

**SECTION 1: IDENTIFICATION**

<b>PRODUCT NAME</b>	<b>ECO-RISE™ "A" Component Synergy Series</b>
<b>CAS NUMBER</b>	Not available
<b>PRODUCT USE</b>	Polyurethane Foam
<b>MANUFACTURER</b>	Specialty Products, Inc. (SPI)
<b>ADDRESS</b>	2410 104th Street Ct S Suite D, Lakewood, WA 98499
<b>PHONE</b>	253-588-7101 (800) 627-0773
<b>FAX</b>	253-588-7196
<b>EMERGENCY CONTACT</b>	FOR SPILLS, LEAKS, FIRE, OR EXPOSURE CALL <b>CHEMTREC</b>
<b>TOLL FREE</b>	<b>800-424-9300</b>
<b>INTERNATIONAL</b>	+1-703-527-3887
<b>FAX</b>	913-321-1490

**SECTION 2: HAZARDS IDENTIFICATION**

**GHS LABEL ELEMENTS**  
GHS PICTOGRAM



**DANGER**

**GHS CLASSIFICATION**

CATEGORY	HAZARD STATEMENTS		
Skin corrosion/irritation	Category 2	H315	Causes skin irritation.
Skin sensitization	Category 1	H317	May cause an allergic skin reaction.
Serious eye damage/eye irritation	Category 2B	H320	Causes eye irritation.
Acute toxicity inhalation	Category 4	H332	Harmful if inhaled.
Respiratory sensitization	Category 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Specific target organ toxicity (STOT), single exposure; respiratory tract	Category 3	H335	May cause respiratory irritation.
Specific target organ toxicity (STOT), repeated exposure	Category 1	H372	Causes damage to organs (respiratory tract) through prolonged or repeated exposure if inhaled.

**PRECAUTIONARY STATEMENTS**

**PREVENTION**

P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink, or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P285	In case of inadequate ventilation wear respiratory protection.

**RESPONSE**

P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P321	Specific treatment (as detailed in this SDS).
P332+P313	IF SKIN irritation occurs: Get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	IF eye irritation persists: Get medical advice/attention.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P304+P312	IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
P342+P311	IF experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P314	Get medical advice/attention if you feel unwell.

**STORAGE**

P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

**DISPOSAL**

P501	Dispose of contents/container in accordance with applicable regional, national and local laws and regulations.
------	----------------------------------------------------------------------------------------------------------------

**READ THE ENTIRE SDS FOR MORE THOROUGH EVALUATION OF THE HAZARDS**



**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

CHEMICAL NAME	CAS NUMBER	% WEIGHT
Polymethylene polyphenylene isocyanate	9016-87-9	30-70
4,4'-Diphenylmethane diisocyanate	101-68-8	30-70

**SECTION 4: FIRST AID MEASURES**

<b>EYE:</b>	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
<b>SKIN:</b>	After contact with skin, wash immediately with plenty of warm, soapy water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. A poly-glycol based skin cleanser or corn oil may be more effective than soap and water. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
<b>INHALATION:</b>	Move exposed person to fresh air. Get medical attention immediately. Treatment is symptomatic for primary irritation or bronchospasm. If breathing is labored, oxygen should be administered by qualified personnel.
<b>INGESTION:</b>	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Provided the patient is conscious, wash out mouth with water. Get medical attention if symptoms appear.
<b>NOTES TO PHYSICIAN:</b>	Symptomatic and supportive therapy as needed. Following severe exposure, medical follow-up should be monitored for 48 hours.

**SECTION 5: FIRE FIGHTING MEASURES**

<b>FLASH POINT:</b>	446°F (230°C) closed cup.
<b>HAZARDS WHEN ON FIRE OR NEAR FLAME:</b>	Toxic fumes may be released in fire situations. Product can decompose at high temperatures forming toxic gases. Closed containers may develop pressure and rupture with prolonged exposure to heat.
<b>SUITABLE EXTINGUISHING MEDIA:</b>	Carbon dioxide, dry chemical powder, foam, water fog or fine spray. Alcohol resistant foams are preferred for large fires. Use water spray to cool fire-exposed containers.
<b>UNSUITABLE EXTINGUISHING MEDIA:</b>	Exercise caution when using water. Water contamination of product will generate carbon dioxide gas. Do not use direct water spray.
<b>SPECIAL EXPOSURE HAZARDS:</b>	Reacts vigorously with water above 122°F (50°C). Closed containers may rupture violently when heated. Polymeric MDI decomposes rapidly above 400°F (204°C).
<b>SPECIAL PROTECTIVE EQUIPMENT FOR FIRE FIGHTERS:</b>	Firefighters should wear full protective gear including self-contained breathing apparatus when fighting chemical fires. Fight fire from a protected location or a safe distance. When using water care must be taken since the reaction between water and hot Polymeric MDI can be vigorous.
<b>HAZARDOUS DECOMPOSITION:</b>	During a fire, products of combustion may include carbon monoxide, carbon dioxide, hydrogen cyanide, nitrogen oxides, dense smoke, and irritating or toxic fumes.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

<b>ACCIDENTAL RELEASE MEASURES:</b>	For major spills call <b>CHEMTREC</b> : Toll free <b>1-800-424-9300</b> for international call <b>1-703-527-3887</b> .
<b>PERSONAL PRECAUTIONS:</b>	Wear appropriate personal protective equipment recommended in SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION of this SDS. Immediately contact emergency personnel. Evacuate the area. Keep upwind avoiding inhalation of vapors. Clean-up should only be performed by trained personnel. People dealing with major spillages should wear full protective clothing including respiratory protection.
<b>ENVIRONMENTAL PRECAUTIONS:</b>	This material may contaminate the environment without proper control and response to spills. Ensure spilled material does not come in contact with soil, waterway, drains, sewers, or other runoff that would further disperse the material. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil, or air). Sources of ignition should be kept clear.
<b>METHODS FOR CONTAINMENT:</b>	Use diking or capping to control migration. Contain and absorb large spillages with a non-flammable absorbent carrier (such as vermiculite, earth, or sand). DO NOT USE combustible materials such as sawdust. Shovel into open-top drums or plastic bags for further decontamination, if necessary. Remove and properly dispose of residues. Dispose of via a licensed waste disposal contractor (See SECTION 13: DISPOSAL CONSIDERATIONS) Notify applicable government authorities if release is reportable.
<b>METHODS FOR CLEANING UP:</b>	Only proceed with clean up by taking the appropriate personal protection measures required and ensure surrounding area does not contain further hazards that could worsen the spill, cause migration, or cause further harm (i.e. eliminate any ignition sources). Move any non-contaminated, non-leaking containers from the spill zone if it can be done safely. Dike, dam, or further restrict and stop active leaks without posing further damage or harm to individuals, the environment, and/or structures. Contain and collect spillage. See SECTION 13: DISPOSAL CONSIDERATIONS for disposal information and SECTION 8: EXPOSURE CONTROL/ PERSONAL PROTECTION for recommended Personal Protective Equipment (PPE). Obey all local, state, and federal regulations during clean up.

## SECTION 7: HANDLING & STORAGE

<b>GENERAL:</b>	Ideal storage temperature is 60-90°F (15-32°C). Handling and storage shall be in accordance with local, state/provincial, or federal regulations.
<b>HANDLING:</b>	Before opening this package, read and follow warning labels on all components. Avoid contact with the product or reaction mixture. Put on appropriate personal protective equipment. Use only with adequate ventilation to ensure that the occupational exposure limit is not exceeded, use respirator when ventilation is inadequate. Avoid breathing aerosols, mists, and vapors. (See SECTION 8: EXPOSURE CONTROL/ PERSONAL PROTECTION for details). Do not ingest. Eating, drinking, and smoking shall be prohibited in areas where this material is handled, stored, and processed. Workers shall wash hands and face before eating, drinking, and smoking. Persons with a history of skin sensitization problems, asthma, allergies, or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Do not get in eyes, on skin, or clothing. Keep in the original container or an approved alternative made from a compatible material. Kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse containers.
<b>STORAGE:</b>	Keep container tightly closed and properly sealed when stored. Keep contents away from moisture. Due to reaction with water producing CO <sub>2</sub> gas, a hazardous build-up of pressure could result if contaminated containers are resealed. DO NOT reseal contaminated containers. Uncontaminated containers, free of moisture, may be resealed and stored after purging the container with argon or nitrogen gas.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>EXPOSURE LIMITS:</b>		
<b>COMPONENT NAME</b>	<b>CAS NUMBER</b>	<b>EXPOSURE LIMITS</b>
Polymethylene polyphenylene isocyanate	9016-87-9	<b>ALBERTA CANADA TWA</b> TWA: 0.005 ppm TWA: 0.07 mg/m <sup>3</sup>
4,4'-Diphenylmethane diisocyanate	101-68-8	<b>ACGIH TLV</b> TWA: 0.005 ppm 8 hour(s) <b>OSHA PEL</b> CEIL: 0.02 ppm CEIL: 0.2 mg/m <sup>3</sup> <b>NIOSH REL</b> CEIL: 0.2 mg/m <sup>3</sup> 10 minute(s) CEIL: 0.02 ppm 10 minute(s) TWA: 0.05 mg/m <sup>3</sup> 10 hour(s) TWA: 0.005 ppm 10 hour(s)
<b>ENGINEERING CONTROLS:</b>	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor, or mist, use process enclosures, local exhaust ventilation, and other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.	
<b>HYGIENE MEASURES:</b>	Wash hands, forearms, and face thoroughly with plenty of soap and water after handling chemical products, before eating, smoking, and using the restroom and at the end of the working period. Appropriate engineering, administrative, and other best practice decontamination control measures must be used to isolate contaminants on clothing and to prevent unintended migration of contaminants. Handle clothing and other potentially contaminated material appropriately and in compliance with local, state, and federal regulations in the process of removing, washing/cleaning, and reuse of these potentially contaminated materials. Ensure compliant use and location of eyewash station and safety showers.	
<b>PERSONAL PROTECTIVE EQUIPMENT (PPE):</b>		
<b>EYE PROTECTION:</b>	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield.	
<b>SKIN PROTECTION:</b>	Personal protective equipment for the body should be selected based on the task being performed, the risks involved, and should be approved by an industrial hygiene specialist before handling this product.	
<b>HANDS PROTECTION:</b>	Chemical resistant gloves complying with applicable health and safety standards shall be worn when handling this product. Protective gloves are those made from butyl rubber, nitrile rubber, or polyvinyl alcohol. Appropriate hazard assessments in conjunction with an evaluation of the protection factors of chemical resistant gloves shall be performed to ensure the protective properties remain intact. It is noted that the time to breakdown of protection factors for different glove manufacturers varies. In the case of mixtures, the protection factors of chemical resistant gloves may be impacted and deteriorate at unpredictable rates without understanding the impact of the substance and the specific protection factors of the chemical resistant gloves.	
<b>RESPIRATORY PROTECTION:</b>	Ensure adequate ventilation. If the respirator is the sole means of protection, use a full-face supplied respirator. Use respirators and components tested and approved under appropriate government standards such as OSHA 29CFR 1910.134, NIOSH (US), or CEN (EU).	
<b>ENVIRONMENTAL EXPOSURE CONTROLS:</b>	Dispose of raw and spent materials and wastes in compliance with all local, state, and federal regulations to prevent potential environmental contamination. Industrial air monitoring may be required to determine any potential environmental hazards to the atmosphere. This monitoring may result in the use of engineering and administrative controls such as filtering and scrubbing systems to mitigate or eliminate potential contaminants.	

**SECTION 9: PHYSICAL & CHEMICAL PROPERTIES**

<b>PHYSICAL STATE:</b>	Liquid	<b>FLASH POINT:</b>	446°F (230°C)
<b>COLOR:</b>	Dark brown	<b>AUTO-IGNITION TEMPERATURE:</b>	Not available
<b>ODOR:</b>	Musty odor	<b>DECOMPOSITION TEMPERATURE:</b>	> 400°F (204°C)
<b>ODOR THRESHOLD:</b>	Not available	<b>EXPLOSIVE LIMITS:</b>	Not explosive
<b>pH:</b>	Not applicable	<b>FLAMMABILITY:</b>	Not available
<b>WATER SOLUBILITY:</b>	Not available	<b>BOILING POINT:</b>	Not available
<b>PARTITION COEFFICIENT:</b>	Not available	<b>BOILING RANGE:</b>	> 400°F (204°C)
<b>SPECIFIC GRAVITY:</b>	1.25±0.005 g/cc @ 77°F (25°C)	<b>MELTING/FREEZING POINT:</b>	Not available
<b>VISCOSITY:</b>	200±50 mPa.s @ 77°F (25°C)	<b>VAPOR PRESSURE:</b>	10-4 mmHg @ 104°F (40°C)
<b>EVAPORATION RATE:</b>	Not available	<b>VAPOR DENSITY:</b>	Not available
<b>VOC:</b>	0 g/L	<b>RELATIVE DENSITY:</b>	10.4±0.05 lbs/gal

**SECTION 10: STABILITY & REACTIVITY**

<b>STABILITY:</b>	This product is stable under normal conditions. Isocyanates are very reactive compounds and are especially highly reactive toward a large number of compounds with active hydrogens, particularly at high temperatures and in the presence of catalysts. May make brittle many plastic and rubber materials.
<b>INCOMPATIBILITY:</b>	Water reacts slowly, forming carbon dioxide and an inert material comprised of polyureas which could rupture closed containers. 4, 4'- methylene dianiline is formed as an intermediate product in this reaction. At temperatures above 122°F (50°C), the reaction becomes progressively more vigorous. Amines, alcohols, acids, and bases may react violently with generation of heat. Metal compounds (e.g. organotin catalysts) may polymerize with generation of heat and pressure.
<b>HAZARDOUS REACTION:</b>	Polymeric MDI may undergo uncontrolled exothermic polymerization upon contact with incompatible materials or if heated above 347°F-399°F (175-204°C). The resulting pressure build-up could rupture closed containers. May cause some corrosion to copper alloys and aluminum.
<b>HAZARDOUS POLYMERIZATION:</b>	Polymerization may occur at elevated temperatures in the presence of alkalis, tertiary amines and metal compounds. Under normal conditions of storage and use, hazardous polymerization should not occur.
<b>CONDITIONS TO AVOID:</b>	Avoid conditions of heat, moisture, and direct sunlight.

**SECTION 11: TOXICOLOGY INFORMATION**

<b>ACUTE HEALTH EFFECTS:</b>	
<b>EYE CONTACT:</b>	Causes serious eye irritation. Contact with liquid, mist and aerosols may cause irritation with redness, swelling, pain, and watering of the eyes.
<b>SKIN CONTACT:</b>	Causes skin irritation and may cause allergic skin reaction. Polymeric MDI can cause mild irritation. Skin sensitization, resulting in dermatitis, may occur in some individuals. Application of single doses of 2.5, 3.9, 6.0 and 9.4 mg/kg Polymeric MDI to abraded skin of rabbits, under a cover for 24 hours, caused only minor, local, reversible skin changes.
<b>INHALATION:</b>	May cause allergy or asthma symptoms or breathing difficulties if inhaled. Polymeric MDI has an extremely low vapor pressure and it is difficult to achieve vapor concentrations necessary for inhalation toxicity testing. Symptoms of severe irritation and deaths occurred at 13.6 mg/m <sup>3</sup> . Less severe irritation and no deaths occurred at 4.9 mg/m <sup>3</sup> . There were no visible effects at 2.2 mg/m <sup>3</sup> .
<b>INGESTION:</b>	Swallowing may result in irritation and corrosion of the mouth, throat, and digestive tract.

<b>ACUTE TOXICITY:</b>				
COMPONENT NAME	CAS NUMBER	LD <sub>50</sub> Oral (mg/kg)	LD <sub>50</sub> Dermal (mg/kg)	LC <sub>50</sub> Inhalation (mg/L/4hrs)
Polymethylene polyphenylene isocyanate	9016-87-9	>10,000 (rat)	>6,200 (rabbit)	0.49 (rat)
4,4'-Diphenylmethane diisocyanate	101-68-8	>2,000 (rat)	>9,400 (rabbit)	0.49 (rat)

<b>POTENTIAL CHRONIC EFFECTS:</b>	
<b>CHRONIC EFFECTS:</b>	Contains material that can cause target organ damage. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
<b>TARGET ORGANS:</b>	Long-term, low-level exposure may cause severe, permanent respiratory impairment.
<b>CARCINOGENICITY:</b>	This material does not contain any component that is considered a human carcinogen by the International Agency for Research on Cancer (IARC), American Conference of Governmental Industrial Hygienists (ACGIH), OSHA or the National Toxicology Program (NTP). IARC has concluded that polymeric MDI and MDI are not classifiable as to their carcinogenicity to humans (Group 3). Although lifetime inhalation of PMDI aerosols by rats resulted in a small number of benign adenomas, they are considered to be of unlikely relevance to occupational exposures. Such aerosols are not encountered outside of the experimental laboratory.
<b>MUTAGENICITY:</b>	No known significant effects or critical hazards.
<b>TERATOGENICITY:</b>	No known significant effects or critical hazards.
<b>FERTILITY EFFECTS:</b>	No known significant effects or critical hazards.
<b>DEVELOPMENTAL EFFECTS:</b>	No known significant effects or critical hazards.
<b>MEDICAL CONDITIONS AGGRAVATED BY OVER-EXPOSURE:</b>	Existing respiratory/pulmonary and skin conditions may be aggravated by overexposure.

### SECTION 12: ECOLOGICAL INFORMATION

<b>ENVIRONMENTAL EFFECTS:</b>	Based on a review of the individual components, this product has low ecotoxicity on aquatic organisms. When in contact with water an inert non-biodegradable solid will be produced. There is no evidence of bio-accumulation occurring.
-------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### SECTION 13: DISPOSAL CONSIDERATION

<b>WASTE DISPOSAL:</b>	By-product wastes or process waste generation should be eliminated and/or minimized when possible. Do not dispose of any contaminants into sanitary sewer systems, storm drains, Publicly Owned Treatment Works (POTW), or any other municipal waste water treatment facility without written approval and agreements for processing wastes with such enterprises. Dispose of raw or unused materials, wastes, and/or by-products in accordance with all applicable local, state, and federal laws. Employ the expertise and knowledge of qualified personnel or contractors in disposal of any and all variants of this product. Ensure material containers are cleaned to the applicable standards before recycling, disposing, or reusing containers. Take special precautions to avoid any cross contamination and potential unknown effects from mixing with other substances. Refer to SECTION 8: EXPOSURE CONTROL/ PERSONAL PROTECTION of this document for personal protection requirements. Disposal to the environment or in violation of environmental protection laws and statutes must be prevented.
------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### SECTION 14: TRANSPORT INFORMATION

<b>PROPER SHIPPING NAME:</b>	
<b>DOT:</b>	Other regulated substance, liquid, n.o.s. (contains: 4,4'-Diphenylmethane diisocyanate) *Single containers less than 5,000 lbs. are not regulated.
<b>TDG:</b>	Not regulated.
<b>IMDG:</b>	Not regulated.
<b>IATA:</b>	Not regulated.

This product could potentially contaminate aquatic and terrestrial environments if not handled in accordance with all precautions, regulations, and laws. Users, transporters, and all other applicable entities must review, follow, and apply any and all necessary precautions and procedures to eliminate and/or minimize potential hazards or risks to aquatic or terrestrial environments.

REGULATORY INFORMATION	UN NUMBER	CLASSES	PG*	LABEL	ADDITIONAL INFORMATION
DOT Classification	NA3082	9	III		<b>Reportable quantity 5,000 lbs. (2,268 kg)</b> Single containers less than 5,000 lbs. are not regulated.

\*PG: Packaging group

## SECTION 15: REGULATORY INFORMATION

<b>U.S. Federal Regulations</b>						
<b>TSCA 8b Inventory:</b>	All components are listed on the TSCA inventory or are exempt.					
<b>TSCA 5a (2):</b>	No components listed.					
<b>TSCA 5e:</b>	No components listed.					
<b>TSCA 12b:</b>	No components listed.					
<b>Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs):</b>	<b>COMPONENT</b>	<b>CAS NUMBER</b>	<b>CONCENTRATION</b>			
	4,4'-Diphenylmethane diisocyanate	101-68-8	30-70%			
<b>Clean Air Act - Ozone Depleting Substances (ODS):</b>	This product does not contain nor is it manufactured with ozone depleting substances.					
<b>SARA 313 Form R - Reporting Requirements:</b>	<b>COMPONENT</b>	<b>CAS NUMBER</b>	<b>CONCENTRATION</b>			
	Polymethylene polyphenylene isocyanate	9016-87-9	30-70%			
	4,4'-Diphenylmethane diisocyanate	101-68-8	30-70%			
<b>SARA 311/312 hazard identification:</b>	Not classified.					
<b>CERCLA Hazardous substances:</b>						
<b>Component</b>	<b>Concentration</b>	<b>Section 302 (TPQ)</b>	<b>Section 313</b>	<b>Section 304 CERCLA RQ</b>	<b>CERCLA reportable quantity</b>	<b>Product reportable quantity</b>
Polymethylene polyphenylene isocyanate	30-70%	Not listed	Listed	Not listed	Not available	Not available
4,4'-Diphenylmethane diisocyanate	30-70%	Not listed	Listed	Not listed	5,000 lbs	18,200 lbs
<b>STATE REGULATIONS:</b>						
<b>PENNSYLVANIA/NEW JERSEY/ MASSACHUSETTS - RTK:</b>	<b>COMPONENT</b>	<b>CAS NUMBER</b>	<b>CONCENTRATION</b>			
	Polymethylene polyphenylene isocyanate	9016-87-9	30-70%			
	4,4'-Diphenylmethane diisocyanate	101-68-8	30-70%			
<b>California Prop 65:</b>	This product does not contain a substance known to the State of California to cause birth defects or other reproductive harm at levels which would require a warning under the statute.					
<b>CANADA</b>						
<b>WHMIS (Canada):</b>	WHMIS Class D-1A: Material causing immediate and serious toxic effects (very toxic). WHMIS Class D-2A: Material causing other toxic effects (very toxic).					
<b>CEPA DSL:</b>	All components are listed or exempted.					
<b>This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.</b>						
<b>INTERNATIONAL LISTS:</b>						
<b>Australia inventory (AICS):</b>	All component substances are present on the inventory of Chemical Substances.					
<b>China inventory (IECSC):</b>	All component substances are present on the Chemical Inventory.					
<b>Japan inventory:</b>	All component substances are present on the inventory- Existing and New Chemical Substances (ENCS). Polymeric MDI 7-872; Methylene diphenyl diisocyanate 4-118.					
<b>Korea inventory:</b>	All component substances are present on the inventory- Existing and Evaluated Chemical Substances. Polymeric MDI KE-21487; Methylene diphenyl diisocyanate KE-23829.					
<b>New Zealand inventory of Chemicals (NZIoC):</b>	All component substances are present on the Chemical Inventory.					

**SECTION 16: OTHER INFORMATION**

NFPA & HMIS	
4	Extreme
3	Serious
2	Moderate
1	Slight
0	No Hazard



**National Fire Protection Association (NFPA)**



HEALTH	1
FLAMMABILITY	2
REACTIVITY	1
SPECIAL INFORMATION	W

**Hazardous Material Information System (HMIS)**

HEALTH	2
FLAMMABILITY	1
REACTIVITY	1
SPECIAL INFORMATION	

**Note: The customer is responsible for determining the PPE code for this material. At the time of publishing, the NFPA/HMIS and the New GHS scale had opposite scales of severity. Check the most recent publications for current information.**

<b>Date of Issue:</b>	2/20/2018
<b>Date of previous issue:</b>	10/7/2016
<b>For Your Protection:</b>	The information and recommendations in this publication is to the best of our knowledge, reliable. The toxicity and risk characteristics of products made by SPI will necessarily differ from the toxicity and risk characteristics that occur when such products are used with other materials during a manufacturing process. The resulting risk characteristics should be determined and made known to ultimate end-users and processors. The user is responsible to comply with all applicable federal, provincial or municipal laws and regulations. SPI MAKES NO WARRANTIES OF ANY KIND, EXPRESSED OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.
<b>Preparation Information:</b>	This SDS supersedes <b>ALL</b> previous SDS versions.