





**SECTION 1: IDENTIFICATION**

PRODUCT NAME ECO-RISE™ 3.0 “B” COMPONENT  
 CAS NUMBER Not available  
 PRODUCT USE Polyurethane foam  
 MANUFACTURER Specialty Products, Inc. (SPI)  
 ADDRESS 2410 104<sup>th</sup> Street Ct S Suite D, Lakewood, WA 98499  
 PHONE 253-588-7101 (800) 627-0773  
 FAX 253-588-7196  
 EMERGENCY CONTACT: FOR SPILLS, LEAKS, FIRE or EXPOSURE CALL **CHEMTREC**  
 TOLL FREE **800-424-9300**  
 INTERNATIONAL +1-703-527-3887  
 FAX 913-321-1490

**SECTION 2: HAZARDS IDENTIFICATION**

**GHS CLASSIFICATION:**

GHS Pictogram	<b>NEW GHS SCALE</b>								
	<div style="display: flex; align-items: center;"> <div style="margin-right: 20px;">  <table border="1" style="font-size: small;"> <tr><td>1</td><td>Extreme</td></tr> <tr><td>2</td><td>Serious</td></tr> <tr><td>3</td><td>Moderate</td></tr> <tr><td>4</td><td>Slight</td></tr> </table> </div> <div style="margin-right: 20px;">  </div> <div style="font-size: x-small;"> <p><b>Health</b></p> <p><b>Flammability</b></p> <p><b>Reactivity</b></p> <p>Specialty Information</p> </div> </div>	1	Extreme	2	Serious	3	Moderate	4	Slight
1	Extreme								
2	Serious								
3	Moderate								
4	Slight								
<b>WARNING</b>	<p style="text-align: center;">Personal Protective Equipment</p> <div style="text-align: center;">  </div>								

**EMERGENCY OVERVIEW:**

**HAZARD STATEMENTS**

H315 Causes skin irritation.  
 H320 Causes eye irritation.  
 H333 May be harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H302 Harmful if swallowed.

**PRECAUTIONARY STATEMENTS**

P264 Wash hands thoroughly after handling.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P261 Avoid breathing dust/fumes/gas/mist/vapors /spray.  
 P271 Use only out doors or in a well-ventilated area.  
 P270 Do not eat, drink, or smoke when using this product.  
 P285 In case of inadequate ventilation wear respiratory protection.

**APPEARANCE, COLOR, ODOR:**

Liquid, amber, amoniacal.

**USA:** This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**READ THE ENTIRE SDS FOR MORE THOROUGH EVALUATION OF THE HAZARDS**



“Proudly Made in the USA”

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS NUMBER	% WEIGHT
Conventional Polyol	Not available	30-60
Polyether polyol	25791-96-2	20-50
Triethanolamine	102-71-6	1-20
Ethanol, 2-(dimethylamino)-	108-01-0	1-20
Dipropylene glycol	25265-71-8	0-10
Triethylenediamine (TEDA)	280-57-9	0-10
Copolymer of dimethylsiloxane and polyoxyalkylene	68937-45-2	0-10
Dibutyltin dilaurylmercaptide	1185-81-5	0-10

### SECTION 4: FIRST AID MEASURES

<b>EYE:</b>	<b>H320</b>	Causes eye irritation. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>SKIN:</b>	<b>H315</b>	Causes skin irritation. If on skin: wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Call a poison center or doctor/physician if you feel unwell.
<b>INHALATION:</b>	<b>H333/335</b>	May be harmful if inhaled and may cause respiratory irritation. If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
<b>INGESTION:</b>	<b>H302</b>	Harmful if swallowed. If swallowed: Rinse mouth. Call a poison center or doctor/physician IF you feel unwell.
<b>NOTES TO PHYSICIAN:</b>		Symptomatic and supportive therapy as needed. Following severe exposure, medical follow-up should be monitored for 48 hours.

### SECTION 5: FIRE FIGHTING MEASURES

<b>FLASH POINT:</b>	Not available
<b>HAZARDS WHEN ON FIRE OR NEAR FLAME:</b>	May produce toxic fumes of carbon dioxide, carbon monoxide, ammonia, ketones, nitrogen oxides, and formaldehyde when near heat source/flame. This product contains Ethanol, 2-(dimethylamino), at 3.7%, may lead to the formation of explosive vapors. When in a closed container, pressure will increase which may lead to a rupture of the container.
<b>SUITABLE EXTINGUISHING MEDIA:</b>	Water, dry extinguishing media, carbon dioxide, foam.
<b>NOT SUITABLE EXTINGUISHING MEDIA:</b>	None known.

**SPECIAL EXPOSURE HAZARDS:** Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. If in a fire or heated, a pressure increase will occur and the container may rupture.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE FIGHTERS:** Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. PVC boots, gloves, safety helmet and protective clothing should be worn.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**ACCIDENTAL RELEASE MEASURES:** For major spills call **CHEMTREC**: Toll free 1-800-424-9300 for international call 1-703-527-3887.

**PERSONAL PRECAUTIONS:** Wear appropriate personal protective equipment recommended in SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION of this SDS. Immediately contact emergency personnel. Evacuate the area. Keep upwind avoiding inhalation of vapors. Clean-up should only be performed by trained personnel. People dealing with major spillages should wear full protective clothing including respiratory protection.

**ENVIRONMENTAL PRECAUTIONS:** This material may contaminate the environment without proper control and response to spills. Ensure spilled material does not come in contact with soil, waterway, drains, sewers, or other runoff that would further disperse the material. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil, or air). Sources of ignition should be kept clear.

**METHODS FOR CONTAINMENT:** Use diking or capping to control migration. Contain and absorb large spillages with a non-flammable absorbent carrier (such as vermiculite, earth, or sand). DO NOT USE combustible materials such as sawdust. Shovel into open-top drums or plastic bags for further decontamination, if necessary. Remove and properly dispose of residues. Dispose of via a licensed waste disposal contractor (See SECTION 13: DISPOSAL CONSIDERATIONS) Notify applicable government authorities if release is reportable.

**METHODS FOR CLEANING UP:** Only proceed with clean up by taking the appropriate personal protection measures required and ensure surrounding area does not contain further hazards that could worsen the spill, cause migration, or cause further harm (i.e. eliminate any ignition sources). Move any non-contaminated, non-leaking containers from the spill zone if it can be done safely. Dike, dam, or further restrict and stop active leaks without posing further damage or harm to individuals, the environment, and/or structures. Contain and collect spillage. See SECTION 13: DISPOSAL CONSIDERATIONS for disposal information and SECTION 8: EXPOSURE CONTROL/ PERSONAL PROTECTION for recommended personal protective equipment (PPE). Obey all local, state, and federal regulations during clean up.

## SECTION 7: HANDLING & STORAGE

- GENERAL:** Ideal storage temperature is 60 – 90°F (15-32°C). Handling and storage shall be in accordance with local, state/provincial, or federal regulations.
- HANDLING:** Before opening this package, read and follow warning labels on all components. Avoid contact with the product or reaction mixture. Put on appropriate personal protective equipment. Use only with adequate ventilation to ensure that the occupational exposure limit is not exceeded, use respirator when ventilation is inadequate. Avoid breathing aerosols, mists, and vapors. (See SECTION 8: EXPOSURE CONTROL /PERSONAL PROTECTION for details). Do not ingest. Eating, drinking, and smoking shall be prohibited in areas where this material is handled, stored, and processed. Workers should wash hands and face before eating, drinking and smoking. Persons with a history of skin sensitization problems, asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Do not get in eyes, on skin, or clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- STORAGE:** Keep containers properly sealed and when stored indoors, in a dry and well-ventilated area. Keep contents away from moisture. Due to reaction with water producing CO<sub>2</sub> gas, a hazardous build-up of pressure could result if contaminated containers are resealed. DO NOT reseat contaminated containers. Uncontaminated containers, free of moisture, may be resealed and stored after purging the container with argon or nitrogen gas. DO NOT store in containers made of copper, copper alloys, or galvanized surfaces.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### EXPOSURE LIMITS

INGREDIENT NAME	CAS NUMBER	EXPOSURE LIMITS
Conventional Polyol	Not available	Not available.
Polyether polyol	25791-96-2	Not available.
Triethanolamine	102-71-6	<b>OSHA</b> TWA: 5.0 ppm STEL: 5.0 ppm
Ethanol, 2-(dimethylamino)-	108-01-0	Not available.
Dipropylene glycol	25265-71-8	Not available.
Triethylenediamine (TEDA)	280-57-9	Not available.
Copolymer of dimethylsiloxane and polyoxyalkylene	68937-45-2	Not available.
Dibutyltin dilaurylmercaptide	1185-81-5	<b>ACGIH</b> TWA: 0.1 mg/m <sup>3</sup> STEL: 0.2 mg/m <sup>3</sup>

		<p><b>OSHA Z1</b> PEL: 0.1 mg/m<sup>3</sup> <b>NIOSH</b> REL: 0.1 mg/m<sup>3</sup></p>
--	--	--

**ENGINEERING CONTROLS:** Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor, or mist, use process enclosures, local exhaust ventilation, and other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**HYGIENE MEASURES:** Wash hands, forearms, and face thoroughly with plenty of soap and water after handling chemical products, before eating, smoking, and using the restroom. Appropriate engineering, administrative, and other best practice decontamination control measures must be used to isolate contaminants on clothing and to prevent unintended migration of contaminants. Handle clothing and other potentially contaminated material appropriately and in compliance with local, state, and federal regulations in the process of removing, washing/cleaning and reuse of these potentially contaminated materials. Ensure compliant use and location of eyewash station and safety showers.

**PERSONAL PROTECTIVE EQUIPMENT (PPE):**

**EYE PROTECTION:** Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield.

**SKIN PROTECTION:** Personal protective equipment for the body should be selected based on the task being performed, the risks involved, and should be approved by an industrial hygiene specialist before handling this product.

**HANDS PROTECTION:** Chemical resistant gloves complying with applicable health and safety standards shall be worn when handling this product. Protective gloves are those made from butyl rubber, nitrile rubber, or polyvinyl alcohol. Appropriate hazard assessments in conjunction with an evaluation of the protection factors of chemical resistant gloves shall be performed to ensure the protective properties remain intact. It is noted that the time to breakdown of protection factors for different glove manufacturers varies. In the case of mixtures, the protection factors of chemical resistant gloves may be impacted and deteriorate at unpredictable rates without understanding the impact of the substance and the specific protection factors of the chemical resistant gloves.

**RESPIRATORY PROTECTION:** Ensure adequate ventilation. Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection,

use a full-face supplied respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

**ENVIRONMENTAL EXPOSURE CONTROLS:**

Dispose of raw and spent materials and wastes in compliance with all local, state, and federal regulations to prevent potential environmental contamination. Industrial air monitoring may be required to determine any potential environmental hazards to the atmosphere. This monitoring may result in the use of engineering and administrative controls such as filtering and scrubbing systems to mitigate or eliminate potential contaminants.

**SECTION 9: PHYSICAL & CHEMICAL PROPERTIES**

<b>PHYSICAL STATE:</b>	Liquid	<b>FLASH POINT:</b>	Not available
<b>COLOR:</b>	Amber	<b>AUTO-IGNITION TEMP:</b>	Not available
<b>ODOR:</b>	Amoniacal	<b>DECOMPOSITION TEMPERATURE:</b>	Not available
<b>ODOR THRESHOLD:</b>	Not available	<b>EXPLOSIVE LIMITS:</b>	Not explosive
<b>pH:</b>	N/A	<b>FLAMMABILITY:</b>	Not available
<b>WATER SOLUBILITY:</b>	Not available	<b>BOILING POINT:</b>	Not available
<b>PARTITION COEFFICIENT:</b>	Not available	<b>BOILING RANGE:</b>	Not available
<b>SPECIFIC GRAVITY:</b>	1.05g/cc (Water=1)	<b>MELTING/FREEZING POINT:</b>	Not available
<b>VISCOSITY:</b>	950 cps @ 25°C	<b>VAPOR PRESSURE:</b>	Not available
<b>EVAPORATION RATE:</b>	Not available	<b>VAPOR DENSITY:</b>	Not available
<b>VOC:</b>	Not available	<b>RELATIVE DENSITY:</b>	8.8 lbs./gal

**SECTION 10: STABILITY & REACTIVITY**

**STABILITY:** Stable when handled and stored at temperatures 60-90°F (15°C-32°C).

**INCOMPATIBILITY:** Will react with isocyanates, oxidizing materials, strong acids, strong bases, copper, copper alloys, galvanize iron.

**HAZARDOUS REACTION:** No information available.

**HAZARDOUS POLYMERIZATION:** No information available.

**CONDITIONS TO AVOID:** Avoid moisture contamination in containers, avoid high temperatures.

**HAZARDOUS DECOMPOSITION:** May emit irritating and harmful fumes which may include: Carbon dioxide, carbon monoxide, nitrogen oxides, ammonia, ketones, nitic acid, silicone dioxide, tin oxide, and formaldehyde when near heat source/flame.

**SECTION 11: TOXICOLOGY INFORMATION**

**SIGNS AND SYMPTOMS OF OVEREXPOSURE/ACUTE HEALTH EFFECTS:**

**EYE CONTACT:** Causes eye irritation.

**SKIN CONTACT:** Causes skin irritation.

**INHALATION:** May cause respiratory irritation, may be harmful if inhaled

**INGESTION/ASPIRATION:** Harmful if swallowed.

**ACUTE TOXICITY:**

INGREDIENT NAME	CAS NUMBER	LD <sub>50</sub> Oral (mg/kg)	LD <sub>50</sub> Dermal (mg/kg)	LC <sub>50</sub> Inhalation (mg/m <sup>3</sup> /4hrs)
Conventional Polyol	Not available	>2,000 (rat)	>2,000 (rabbit)	Not available
Polyether polyol	25791-96-2	Not available	Not available	Not available
Dipropylene glycol	25265-71-8	14,800 (rat)	20,500 (rabbit)	6,000-8,000 (rat) 8 hrs
Triethylenediamine (TEDA)	280-57-9	3,200 (rat)	>2,000 (rabbit)	10,100 (rat)
Copolymer of dimethylsiloxane and polyoxyalkylene	68937-45-2	Not available	Not available	Not available
Triethanolamine	102-71-6	Not available	Not available	Not available
Ethanol, 2-(dimethylamino)-	108-01-0	1,180 (rat)	2,000 (rabbit)	1,000-2,500 (rat)
Dibutyltin dilaurylmercaptide	1185-81-5	240 (rat)	1,000 (rabbit)	0 1hr

**POTENTIAL CHRONIC EFFECTS**

**CHRONIC EFFECTS:** Repeated ingestion or swallowing may injure internally.

**TARGET ORGANS:** None known.

**CARCINOGENICITY:** As of this publication, this material is not listed on the National Toxic Program (NTP) Report of Carcinogens. Please refer to the most recent information with NTP

**MUTAGENICITY:** No known significant effects or critical hazards.

**TERATOGENICITY:** No known significant effects or critical hazards.

**FERTILITY EFFECT:** No known significant effects or critical hazards.

**DEVLEOPMENTAL EFFECTS:** No known significant effects or critical hazards.

**MEDICAL CONDITIONS AGGRAVATED BY OVER-EXPOSURE:** Existing respiratory/pulmonary conditions may be aggravated by overexposure.

**SECTION 12: ECOLOGICAL INFORMATION**

**ENVIRONMENTAL EFFECTS:** Based on a review of the individual components this product may be immediately harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment and is not readily biodegradable.

## SECTION 13: DISPOSAL CONSIDERATION

**WASTE DISPOSAL:** By-product wastes or process waste generation shall be eliminated and/or minimized when possible. Do not dispose of any contaminants into sanitary sewer systems, storm drains, Publicly Owned Treatment Works (POTW), or any other municipal waste water treatment without written approval and agreements for processing wastes with such enterprises. Dispose of raw or unused materials, wastes, and/or by-products in accordance with all applicable local, state, and federal laws. Employ the expertise and knowledge of qualified personnel or contractors in disposal of any and all variants of this product. Ensure material containers are cleaned to the applicable standards before recycling, disposing, or reusing containers. Take special precautions to avoid any cross contamination and potential unknown effects from mixing with other substances. Refer to SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION of this document for personal protection requirements. Disposal to the environment or in violation of environmental protection laws and statutes must be prevented.

## SECTION 14: TRANSPORT INFORMATION

**PROPER SHIPPING NAME:**

DOT:	Not regulated.
TDG:	Not regulated.
IMDG:	Not regulated.
IATA:	Not regulated.

This product could potentially contaminate aquatic and terrestrial environments if not handled in accordance with all precautions, regulations, and laws. Users, transporters, and all other applicable entities must review, follow, and apply any and all necessary precautions and procedures to eliminate and/or minimize potential hazards or risks to aquatic or terrestrial environments.

## SECTION 15: REGULATORY INFORMATION

**U.S. Federal Regulations**

This material is classified as hazardous under OSHA Hazard Communication Standard (29 CFR 1910.1200)

**HCS Classification:** Toxic  
Irritant

**TSCA 8b Inventory:** All components are listed on the TSCA inventory or are exempt.

**TSCA 5a(2):** No components listed.

**TSCA 5e:** No components listed.



**TSCA 12b:** No components listed.

**Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs):** No components listed.

**Clean Air Act – Ozone Depleting Substances (ODS):** This product does not contain nor is it manufactured with ozone depleting substances.

**SARA 313 Form R-Reporting Requirements:** No components listed.

**SARA 311/312:** Acute health hazard, chronic health hazard.

**CERCLA Hazardous substances:** No components listed

**STATE REGULATIONS:**

**PENNSYLVANIA/ NEW JERSEY/MASSACUSETTS – RTK:**

COMPONENT	CAS NUMBER	CONCENTRATION
Dipropylene glycol	25265-71-8	0-10 %
Ethanol, 2-(dimethylamino)-	108-01-0	1-20 %

**California Prop 65:** This product contains no listed substances known to the State of California to cause cancer, birth defects, or other reproductive harm, at levels which would require a warning under the statute.

**CANADA:**

**WHMIS (Canada):**

COMPONENT	CAS NUMBER	CONCENTRATION
Ethanol, 2-(dimethylamino)-	108-01-0	0-10%

WHMIS Class D-2A: Material causing other toxic effects(very toxic)  
WHMIS Class D-2B: Material causing other toxic effects (toxic)


**This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.**

**INTERNATIONAL LISTS:**

**Australia inventory (AICS):** Information not available.  
**China inventory (IECSC):** Information not available.  
**Japan inventory:** Information not available.  
**Korea inventory:** Information not available.  
**New Zealand inventory of Chemicals (NZIoC):** Information not available.  
**Philippines inventory (PICCS):** Information not available


**SECTION 16: OTHER INFORMATION**

4	Extreme
3	Serious
2	Moderate
1	Slight
0	No Hazard



**National Fire Protection Association (NFPA)**

**Hazardous Material Information System (HMIS)**



Health	1
Flammability	1
Reactivity	0
PPE	

**Note: The customer is responsible for determining the PPE code for this material. At the time of publishing, the NFPA/HMIS and the New GHS scale had opposite scales of severity. Check the most recent publications for current information.**

**Date of Issue:**  
**Date of previous issue:**  
**For Your Protection:**

03/23/2015  
12/30/2014  
The information and recommendations in this publication is to the best of our knowledge, reliable. The toxicity and risk characteristics of products made by SPI will necessarily differ from the toxicity and risk characteristics that occur when such products are used with other materials during a manufacturing process. The resulting risk characteristics should be determined and made known to ultimate end-users and processors. The user is responsible to comply with all applicable federal, provincial or municipal laws and regulations. SPI MAKES NO WARRANTIES OF ANY KIND, EXPRESSED OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

**Preparation Information:** This SDS supersedes ALL previous SDS versions.