



SAFETY DATA SHEET

EPL™ 4 "B" Component

Revised Date: 4/26/2016

Version: 2 SDS-292

SECTION 1: IDENTIFICATION

PRODUCT NAME
CAS NUMBER
PRODUCT USE

MANUFACTURER

ADDRESS PHONE

FAX

EMERGENCY CONTACT

TOLL FREE INTERNATIONAL FAX

EPL™ 4 "B" Component Synergy Series

Not available Polyurea Coating

Specialty Products, Inc. (SPI)

2410 104th Street Ct S Suite D, Lakewood, WA 98499

253-588-7101 (800) 627-0773

253-588-7196

FOR SPILLS, LEAKS, FIRE, OR EXPOSURE CALL CHEMTREC

800-424-9300 +1-703-527-3887 913-321-1490

SECTION 2: HAZARDS IDENTIFICATION

SECTION 2. HALARDS IDENTIFICATION

GHS PICTO	GRAM

GHS CLASSIFICATION

GHS SCALE	
1	Extreme
2	Serious
3	Moderate
4	Slight







WARNING

Personal Protective Equipment







NEW GHS SCALE





EMERG	EMERGENCY OVERVIEW		
	HAZARD STATEMENTS		PRECAUTIONARY STATEMENTS
H315	Causes skin irritation.	P261	Avoid breathing dust/fume/gas/mist vapors/spray.
H317	May cause an allergic skin reaction.	P264	Wash hands thoroughly after handling.
H320	Causes eye irritation.	P280	Wear protective gloves/protective clothing/eye protection/face protection.
H302	Harmful if swallowed.	P270	Do not eat, drink, or smoke when using this product.
H333	My be harmful if inhaled.	P271	Use only outdoors or in a well-ventilated area.
H335	May cause respiratory irritation.	P285	In case of inadequate ventilation wear respiratory protection.

APPEARANCE, COLOR, ODOR:

Liquid, brown, amine odor.

USA: This material is not considered hazardous to health by the OSHA Hazard Communication Standard (29 CFR 1910-1200).

READ THE ENTIRE SDS FOR MORE THOROUGH EVALUATION OF THE HAZARDS

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

SECTION S. SOMI SCHOOL IN CHARACTER OF INSTRUMENTS		
CHEMICAL NAME	CAS NUMBER	% WEIGHT
*Proprietary	Not available	30-70
Di-(methylthio) toluenediamine	106264-79-3	10-20
Glyceryl poly (oxypropylene) triamine	64852-22-8	10-20
N,N-dialkylamino-diphenylmethane	5285-60-9	1-10
Diethylmethylbenzenediamine	68479-98-1	1-10
Triethyl orthoformate	122-51-0	<1
Fatty acid ester	Not available	<1

*The specific chemical identity and exact percentage (concentration) is withheld as a trade secret per applicable regulations and statutes.





SECTION 4: FIRS	T AID MEASURE	es
EYE:	H320	Causes eye irritation. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF eye irritation persists: Get medical advice/attention.
SKIN:	H315/H317	Causes skin irritation and may cause an allergic skin reaction. IF ON SKIN: wash with plenty of soap and water. IF SKIN irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
INHALATION:	H333/335	May be harmful if inhaled and may cause respiratory irritation. IF INHALED: remove victim to fresh air and Keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
INGESTION:	H302	Harmful if swallowed. IF SWALLOWED: Rinse mouth. Do not induce vomiting. Call a POISON CENTER or doctor/physician IF you feel unwell.
NOTES TO PHYS	ICIAN:	Symptomatic and supportive therapy as needed. Following severe exposure, medical follow-up should be monitored for 48 hours.
SECTION 5: FIRE	FIGHTING MEAS	SURES
FLASH POINT:		Not available.
HAZARDS WHEN NEAR FLAME:	I ON FIRE OR	May produce toxic fumes of carbon dioxide, carbon monoxide, and/or nitrogen oxides when near heat source/flame. When in a closed container, pressure will increase which may lead to a rupture of the container.
SUITABLE EXTIN MEDIA:	GUISHING	Dry chemical, carbon dioxide, water spray or regular foam.
UNSUITABLE EXT	TINGUISHING	None known.
SPECIAL EXPOSE	URE HAZARDS:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. If in a fire or heated, a pressure increase will occur and the container may rupture.
SPECIAL PROTECT EQUIPMENT FOR FIGHTERS:		Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. PVC boots, gloves, safety helmet and protective clothing should be worn.
SECTION 6: ACCI	DENTAL RELEAS	SE MEASURES
ACCIDENTAL REI	LEASE	For major spills call CHEMTREC : Toll free 1-800-424-9300 for international call 1-703-527-3887 .
PERSONAL PREC	CAUTIONS:	Wear appropriate personal protective equipment recommended in SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION of this SDS. Immediately contact emergency personnel. Evacuate the area. Keep upwind avoiding inhalation of vapors. Clean-up should only be performed by trained personnel. People dealing with major spillages should wear full protective clothing including respiratory protection.
ENVIRONMENTA PRECAUTIONS:	L	This material may contaminate the environment without proper control and response to spills. Ensure spilled material does not come in contact with soil, waterway, drains, sewers, or other runoff that would further disperse the material. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil, or air). Sources of ignition should be kept clear.
METHODS FOR C	CONTAINMENT:	Use diking or capping to control migration. Contain and absorb large spillages with a non-flammable absorbent carrier (such as vermiculite, earth, or sand). DO NOT USE combustible materials such as sawdust. Shovel into open-top drums or plastic bags for further decontamination, if necessary. Remove and properly dispose of residues. Dispose of via a licensed waste disposal contractor (See SECTION 13: DISPOSAL CONSIDERATIONS) Notify applicable government authorities if release is reportable.

METHODS FOR CLEANING UP:	Only proceed with clean up by taking the appropriate personal protection measures required and ensure surrounding area does not contain further hazards that could worsen the spill, cause migration, or cause further harm (i.e. eliminate any ignition sources). Move any non-contaminated, non-leaking containers from the spill zone if it can be done safely. Dike, dam, or further restrict and stop active leaks without posing further damage or harm to individuals, the environment, and/or structures. Contain and collect spillage. See SECTION 13: DISPOSAL CONSIDERATIONS for disposal information and SECTION 8: EXPOSURE CONTROL/ PERSONAL PROTECTION for recommended Personal Protective Equipment (PPE). Obey all local, state, and federal regulations during clean up.
SECTION 7: HANDLING & STOR	AGE
GENERAL:	Ideal storage temperature is 60-90°F (15-32°C). Handling and storage shall be in accordance with local, state/provincial, or federal regulations.
HANDLING:	Before opening this package, read and follow warning labels on all components. Avoid contact with the product or reaction mixture. Put on appropriate personal protective equipment. Use only with adequate ventilation to ensure that the occupational exposure limit is not exceeded, use respirator when ventilation is inadequate. Avoid breathing aerosols, mists, and vapors. (See SECTION 8: EXPOSURE CONTROL/ PERSONAL PROTECTION for details). Do not ingest. Eating, drinking, and smoking shall be prohibited in areas where this material is handled, stored, and processed. Workers shall wash hands and face before eating, drinking, and smoking. Persons with a history of skin sensitization problems, asthma, allergies, or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Do not get in eyes, on skin, or clothing. Keep in the original container or an approved alternative made from a compatible material. Kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse containers.
STORAGE:	Keep container tightly closed and properly sealed when stored. When possible, store product indoors in a dry, well-ventilated area. Store in original container protected from direct sunlight, away from incompatible materials, and away from food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers and use appropriate containment to avoid environmental contamination.
SECTION 8: EXPOSURE CONTR	OLS/PERSONAL PROTECTION
EXPOSURE LIMITS:	As of the latest revision of this document, no known exposure limits exist for this product. The absence of current exposure data does not relieve an employer, user, or other to determine the specific hazards and appropriate exposure protection measures in the application and use of this product. Personal, workplace, atmospheric, and/or biological monitoring may be required to determine the effectiveness of engineering, administrative, and/or other best practice control measures. These monitoring results determine the need for and type of respiratory protective equipment, if any. Refer to the appropriate local, state, and federal regulations and statutes for the most current information and for guidance in the determination of hazardous conditions and the correlating personal protective equipment.
ENGINEERING CONTROLS:	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor, or mist, use process enclosures, local exhaust ventilation, and other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
HYGIENE MEASURES:	Wash hands, forearms, and face thoroughly with plenty of soap and water after handling chemical products, before eating, smoking, and using the restroom and at the end of the working period. Appropriate engineering, administrative, and other best practice decontamination control measures must be used to isolate contaminates on clothing and to prevent unintended migration of contaminants. Handle clothing and other potentially contaminated material appropriately and in compliance with local, state, and federal regulations in the process of removing, washing/cleaning, and reuse of these potentially contaminated materials. Ensure compliant use and location of eyewash station and safety showers.

PERSONAL PROTECTIVE EQUIPMENT (PPE):			
EYE PROTECTION:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield.		
SKIN PROTECTION:		or the body should be selected based nd should be approved by an industrial	
HANDS PROTECTION:	Chemical resistant gloves complying with applicable health and safety standards shall be worn when handling this product. Protective gloves are those made from butyl rubber, nitrile rubber, or polyvinyl alcohol. Appropriate hazard assessments in conjunction with an evaluation of the protection factors of chemical resistant gloves shall be performed to ensure the protective properties remain intact. It is noted that the time to breakdown of protection factors for different glove manufacturers varies. In the case of mixtures, the protection factors of chemical resistant gloves may be impacted and deteriorate at unpredictable rates without understanding the impact of the substance and the specific protection factors of the chemical resistant gloves.		
RESPIRATORY PROTECTION:	Ensure adequate ventilation. Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).		
ENVIRONMENTAL EXPOSURE CONTROLS:	Dispose of raw and spent materials and wastes in compliance with all local, state, and federal regulations to prevent potential environmental contamination. Industrial air monitoring may be required to determine any potential environmental hazards to the atmosphere. This monitoring may result in the use of engineering and administrative controls such as filtering and scrubbing systems to mitigate or eliminate potential contaminants.		
SECTION 9: PHYSICAL & C	CHEMICAL PROPERTIES		
PHYSICAL STATE:	Liquid	FLASH POINT:	Not available
COLOR:	Brown	AUTO-IGNITION TEMPERATURE:	Not available
ODOR:	Amine odor	DECOMPOSITION TEMPERATURE:	Not available
ODOR THRESHOLD:	Not available	EXPLOSIVE LIMITS:	Not explosive
l	<u> </u>	EXPEOSIVE LIMITS.	TTOT CAPICOITE
pH:	Not applicable	FLAMMABILITY:	Not available
PH: WATER SOLUBILITY:	Not applicable Not available		· · · · · · · · · · · · · · · · · · ·
•	· · ·	FLAMMABILITY:	Not available
WATER SOLUBILITY:	Not available	FLAMMABILITY: BOILING POINT:	Not available Not available
WATER SOLUBILITY: PARTITION COEFFICIENT:	Not available Not available	FLAMMABILITY: BOILING POINT: BOILING RANGE:	Not available Not available Not available
WATER SOLUBILITY: PARTITION COEFFICIENT: SPECIFIC GRAVITY:	Not available Not available 1.025±0.005 g/cc @ 77°F (25°C)	FLAMMABILITY: BOILING POINT: BOILING RANGE: MELTING/FREEZING POINT:	Not available Not available Not available Not available
WATER SOLUBILITY: PARTITION COEFFICIENT: SPECIFIC GRAVITY: VISCOSITY:	Not available Not available 1.025±0.005 g/cc @ 77°F (25°C) 1,000±100 cps @ 77°F (25°C)	FLAMMABILITY: BOILING POINT: BOILING RANGE: MELTING/FREEZING POINT: VAPOR PRESSURE:	Not available Not available Not available Not available Not available
WATER SOLUBILITY: PARTITION COEFFICIENT: SPECIFIC GRAVITY: VISCOSITY: EVAPORATION RATE:	Not available Not available 1.025±0.005 g/cc @ 77°F (25°C) 1,000±100 cps @ 77°F (25°C) Not available Not available	FLAMMABILITY: BOILING POINT: BOILING RANGE: MELTING/FREEZING POINT: VAPOR PRESSURE: VAPOR DENSITY:	Not available
WATER SOLUBILITY: PARTITION COEFFICIENT: SPECIFIC GRAVITY: VISCOSITY: EVAPORATION RATE: VOC:	Not available Not available 1.025±0.005 g/cc @ 77°F (25°C) 1,000±100 cps @ 77°F (25°C) Not available Not available REACTIVITY	FLAMMABILITY: BOILING POINT: BOILING RANGE: MELTING/FREEZING POINT: VAPOR PRESSURE: VAPOR DENSITY:	Not available
WATER SOLUBILITY: PARTITION COEFFICIENT: SPECIFIC GRAVITY: VISCOSITY: EVAPORATION RATE: VOC: SECTION 10: STABILITY &	Not available Not available 1.025±0.005 g/cc @ 77°F (25°C) 1,000±100 cps @ 77°F (25°C) Not available Not available REACTIVITY	FLAMMABILITY: BOILING POINT: BOILING RANGE: MELTING/FREEZING POINT: VAPOR PRESSURE: VAPOR DENSITY: RELATIVE DENSITY: at temperatures 60-90°F (15-32°C).	Not available
WATER SOLUBILITY: PARTITION COEFFICIENT: SPECIFIC GRAVITY: VISCOSITY: EVAPORATION RATE: VOC: SECTION 10: STABILITY & STABILITY:	Not available Not available 1.025±0.005 g/cc @ 77°F (25°C) 1,000±100 cps @ 77°F (25°C) Not available Not available REACTIVITY Stable when handled and stored	FLAMMABILITY: BOILING POINT: BOILING RANGE: MELTING/FREEZING POINT: VAPOR PRESSURE: VAPOR DENSITY: RELATIVE DENSITY: at temperatures 60-90°F (15-32°C).	Not available
WATER SOLUBILITY: PARTITION COEFFICIENT: SPECIFIC GRAVITY: VISCOSITY: EVAPORATION RATE: VOC: SECTION 10: STABILITY & STABILITY: INCOMPATIBILITY:	Not available Not available 1.025±0.005 g/cc @ 77°F (25°C) 1,000±100 cps @ 77°F (25°C) Not available Not available REACTIVITY Stable when handled and stored Strong reaction with acids and on the specific data available.	FLAMMABILITY: BOILING POINT: BOILING RANGE: MELTING/FREEZING POINT: VAPOR PRESSURE: VAPOR DENSITY: RELATIVE DENSITY: at temperatures 60-90°F (15-32°C).	Not available Not available Not available Not available Not available Not available 8.55±0.05 lbs/gal
WATER SOLUBILITY: PARTITION COEFFICIENT: SPECIFIC GRAVITY: VISCOSITY: EVAPORATION RATE: VOC: SECTION 10: STABILITY & STABILITY: INCOMPATIBILITY: HAZARDOUS REACTION: HAZARDOUS	Not available Not available 1.025±0.005 g/cc @ 77°F (25°C) 1,000±100 cps @ 77°F (25°C) Not available Not available REACTIVITY Stable when handled and stored Strong reaction with acids and or not available. Hazardous polymerization will not avoid temperatures above 100°F	FLAMMABILITY: BOILING POINT: BOILING RANGE: MELTING/FREEZING POINT: VAPOR PRESSURE: VAPOR DENSITY: RELATIVE DENSITY: at temperatures 60-90°F (15-32°C). xidizing agents.	Not available Not available Not available Not available Not available Not available 8.55±0.05 lbs/gal

SECTION 11: TOXICOLOGY INFOR	MATION					
ACUTE HEALTH EFFECTS:						
EYE CONTACT:	Causes eye irritati	Causes eye irritation.				
SKIN CONTACT:	Causes skin irritati	Causes skin irritation and may cause an allergic skin reaction.				
INHALATION:	May be harmful if	inhaled and may cau	se respiratory irritatio	n.		
INGESTION:	Harmful if swallow	red.				
ACUTE TOXICITY:						
COMPONENT NAME	CAS NUMBER	LD ₅₀ Oral (mg/kg)	LD ₅₀ Dermal (mg/kg)	LC ₅₀ Inhalation (mg/m³/4hrs)		
Di-(methylthio) toluenediamine	106264-79-3	1,515 (rat)	2,000 (rabbit)	189 (rat)		
Glyceryl poly (oxypropylene) triamine	64852-22-8	2,690 (rat)	12,500 (rabbit)	Not available		
N,N-dialkylamino-diphenylmethane	5285-60-9	1,380 (rat)	3,090 (rabbit)	Not available		
Diethylmethylbenzenediamine	68479-98-1	738 (rat)	>2,000 (rabbit)	Not available		
Triethyl orthoformate	122-51-0	Not available	Not available	Not available		
Fatty acid ester	Not available	Not available	Not available	Not available		
POTENTIAL CHRONIC EFFECTS:						
CHRONIC EFFECTS:	A two year study on rats showed that diethylmethylbenzenediamine caused effects in the pancreas, liver, thyroid, and eyes. There was increase in the number of tumors in the liver and thyroid of male rats. An increase in the number of tumors in the liver and possibly mammary glands of female rats was also found.					
TARGET ORGANS:	Pancreas, liver, thy	roid, and eyes.				
CARCINOGENICITY:	As of this publicati Report of Carcinog	on, this material is no gens. Please refer to	ot listed on the Nation the most recent infor	al Toxic Program (NTP) mation with NTP.		
MUTAGENICITY:	No known significa	ant effects or critical	hazards.			
TERATOGENICITY:	 	ant effects or critical				
FERTILITY EFFECTS:	<u> </u>	ant effects or critical l				
DEVELOPMENTAL EFFECTS: MEDICAL CONDITIONS	<u> </u>	ant effects or critical I		garavated by averavpacure		
AGGRAVATED BY OVER-EXPOSURE:	Existing respiratory/pulmonary and skin conditions may be aggravated by overexposure.					
SECTION 12: ECOLOGICAL INFOR	RMATION					
ENVIRONMENTAL EFFECTS:	Based on a review of the individual components, this product may be immediately harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment, and not readily biodegradable.					
SECTION 13: DISPOSAL CONSIDERATION						
WASTE DISPOSAL:	By-product wastes or process waste generation should be eliminated and/or minimized when possible. Do not dispose of any contaminants into sanitary sewer systems, storm drains, Publicly Owned Treatment Works (POTW), or any other municipal waste water treatment facility without written approval and agreements for processing wastes with such enterprises. Dispose of raw or unused materials, wastes, and/or by-products in accordance with all applicable local, state, and federal laws. Employ the expertise and knowledge of qualified personnel or contractors in disposal of any and all variants of this product. Ensure material containers are cleaned to the applicable standards before recycling, disposing, or reusing containers. Take special precautions to avoid any cross contamination and potential unknown effects from mixing with other substances. Refer to SECTION 8: EXPOSURE CONTROL/ PERSONAL PROTECTION of this document for personal protection requirements. Disposal to the environment or in violation of environmental protection laws and statutes must be prevented.					

PROPER SHIPPING NAME DOT: Not regulated. TDG: Not regulated. IMDG: Not regulated. IATA: Not regulated.

This product could potentially contaminate aquatic and terrestrial environments if not handled in accordance with all precautions, regulations, and laws. Users, transporters, and all other applicable entities must review, follow, and apply any and all necessary precautions and procedures to eliminate and/or minimize potential hazards or risks to aquatic or terrestrial environments.

SECTION 15: REGULATORY INFORMATION

U.S. Federal Regulations			
This material is not considered hazard	dous to health under OSHA Hazard Com	nmunication Standard (29	CFR 1910.1200)
HCS Classification:	Toxic Irritant		
TSCA 8b Inventory:	All components are listed on the TSCA	A inventory or are exempt	•
TSCA 5a (2):	No components listed.		
TSCA 5e:	No components listed.		
TSCA 12b:	No components listed.		
Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs):	No components listed.		
Clean Air Act - Ozone Depleting Substances (ODS):	This product does not contain nor is it	manufactured with ozone	e depleting substances.
SARA 313 Form R - Reporting Requirements:	COMPONENT	CAS NUMBER	CONCENTRATION
Requirements.	Diethylmethylbenzenediamine	68479-98-1	1-10%
SARA 311/312 hazard identification:	Immediate (acute) health hazard. Delayed (chronic) health hazard.		
CERCLA Hazardous substances:	No components listed.		
STATE REGULATIONS:			
PENNSYLVANIA/NEW JERSEY/ MASSACHUSETTS - RTK:	No components listed.		
California Prop 65:	This product contains no listed substances known to the State of California to cause cancer, birth defects, or other reproductive harm, at levels which would require a warning under the statute.		
CANADA			
WHMIS (Canada):	WHMIS Class D-1B: Material causing in	nmediate and serious toxi	ic effects (toxic).
CEPA DSL:	All components are listed or exempted	d.	
This product has been classified and the SDS contains all the info	in accordance with the hazard crite rmation required by the Controlled	eria of the Controlled Products Regulations	Products Regulations s.
INTERNATIONAL LISTS:			
Australia inventory (AICS):	At least one component is not listed.		
China inventory (IECSC):	All components are listed or exempted.		
Japan inventory:	All components are listed or exempted	d.	
Korea inventory:	All components are listed or exempted	d.	
New Zealand inventory of Chemicals (NZIoC):	All components are listed or exempted	d.	
Phillipines inventory (PICCS):	All components are listed or exempted	<u></u> d.	

SECTION 16: OTHER INFORMATION

NFPA & HMIS	
4	Extreme
3	Serious
2	Moderate
1	Slight
0	No Hazard



National Fire Protection Association (NFPA)





Hazardous Material Information System (HMIS)

HEALTH	2
FLAMMABILITY	1
REACTIVITY	0
SPECIAL	
INFORMATION	

Note: The customer is responsible for determining the PPE code for this material. At the time of publishing, the NFPA/HMIS and the New GHS scale had opposite scales of severity. Check the most recent publications for current information.

Date of Issue:	4/26/2016
Date of previous issue:	2/12/2016
For Your Protection:	The information and recommendations in this publication is to the best of our knowledge, reliable. The toxicity and risk characteristics of products made by SPI will necessarily differ from the toxicity and risk characteristics that occur when such products are used with other materials during a manufacturing process. The resulting risk characteristics should be determined and made known to ultimate end-users and processors. The user is responsible to comply with all applicable federal, provincial or municipal laws and regulations. SPI MAKES NO WARRANTIES OF ANY KIND, EXPRESSED OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.
Preparation Information:	This SDS supersedes ALL previous SDS versions.