



SAFETY DATA SHEET

AQUASEAL™ "B" Component Revised Date: 10/19/2018 Version: 8

SDS-162

SECTION 1: IDENTIFICATION

PRODUCT NAME **CAS NUMBER PRODUCT USE MANUFACTURER ADDRESS PHONE** FAX **EMERGENCY CONTACT TOLL FREE** INTERNATIONAL

FAX

P405

P501

AQUASEAL™ "B" Component Synergy Series

Not available Polyurea Coating Specialty Products, Inc. (SPI)

2410 104TH ST. CT. S. STE D LAKEWOOD, WA 98499

253 588 7101 800 627 0773

253 588 7196

FOR SPILLS, LEAKS, FIRE, OR EXPOSURE CALL CHEMTREC

800 424 9300 +1 703 527 3887 913 321 1490

SECTION 2: HAZARDS IDENTIFICATION

GHS LABEL ELEMENTS

GHS PICTOGRAM







WARNING

WAINTING							
GHS CLASSIFICATION							
CATEGORY			HAZARD STATEMENTS				
Acute toxicity oral	Category 4	H302	Harmful if swallowed.				
Skin corrosion/irritation	Category 2	H315	Causes skin irritation.				
Skin sensitization	Category 1C	H317	May cause an allergic skin reaction.				
Serious eye damage/eye irritation	Category 2A	H319	Causes serious eye irritation.				
Germ cell mutagenicity	Category 2	H341	Suspected of causing genetic defects.				
Reproductive toxicity	Category 2	H361d	Suspected of damaging the unborn child.				
Acute hazard aquatic environment	Category 3	H402	Harmful to aquatic life.				
Long-term hazard aquatic environment	Category 2	H411	Toxic to aquatic life with long lasting effects.				

PRECAUTIONARY STATEMENTS

	PREVENTION					
P201	Obtain special instructions before use.					
P202	Do not handle until all safety precautions have been read and understood.					
P260	Do not breathe dust/fume/gas/mist/vapors/spray.					
P264	Wash hands thoroughly after handling.					
P270	Do not eat, drink, or smoke when using this product.					
P273	Avoid release to the environment.					
P280	Wear protective gloves/protective clothing/eye protection/face protection.					
	RESPONSE					
P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician IF you feel unwell.					
P330	Rinse mouth.					
P302+P352	IF ON SKIN: Wash with plenty of soap and water.					
P312	Call a POISON CENTER or doctor/physician if you feel unwell.					
P322	Specific measures (see section 4 on this SDS).					
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.					
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse SKIN with water/shower.					
P363	Wash contaminated clothing before reuse.					
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.					
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.					
P310	Immediately call a POISON CENTER or doctor/physician.					
P321	Specific treatment (see section 4 on this SDS).					
P391	Collect spillage. Hazardous to the aquatic environment.					

STORAGE

DISPOSAL

Dispose of contents/container in accordance with applicable regional, national and local laws and regulations.



Store locked up.

SECTION 3: COMPOSITION/INFO	DRMATION ON INGREDIENTS						
CHEMICAL NAME		CAS NUMBER	% WEIGHT				
*Proprietary		Not available	20-40				
Polyoxypropylenediamine	9046-10-0	10-30					
Glyceryl poly (oxypropylene) triamine	64852-22-8	1-10					
Diethylmethylbenzenediamine		68479-98-1	1-10				
N,N-dialkylamino-diphenylmethane		5285-60-9	1-10				
Dimethylthiotoluenediamine		106264-79-3	1-10				
Ethyl orthoformate		122-51-0	1-10				
*The specific chemical identity and exact p	ercentage (concentration) is withheld as a trade secret per a	applicable regulations	and statutes.				
SECTION 4: FIRST AID MEASURI	ES						
EYE:	In case of contact with the eyes, rinse immediately for at I Get medical attention if symptoms occur.	east 15 minutes with	plenty of water.				
SKIN:	Wash affected areas thoroughly with soap and water. Get	medical attention if s	symptoms occur.				
INHALATION:	Remove the affected individual into fresh air and keep the necessary. Get medical attention if symptoms occur.	e person calm. Assist	in breathing if				
INGESTION:	Rinse mouth and then drink plenty of water. Do not induce give anything by mouth if the victim is unconscious or havif symptoms occur.	e vomiting. Never ind ving convulsions. Get	uce vomiting or medical attention				
NOTES TO PHYSICIAN:	Symptomatic and supportive therapy as needed. Following should be monitored for 48 hours.	ng severe exposure,	medical follow-up				
SECTION 5: FIRE FIGHTING MEAS	SURES						
FLASH POINT:	>378°F (192°C).						
HAZARDS WHEN ON FIRE OR NEAR FLAME:	May produce toxic fumes of carbon dioxide and carbon monoxide when near heat source/flame. When in a closed container, pressure will increase which may lead to a rupture of the container.						
SUITABLE EXTINGUISHING MEDIA:	Dry chemical foam, carbon dioxide, foam, or water spray (mist/foa) to extinguis	า.				
UNSUITABLE EXTINGUISHING MEDIA:	None known.	g,g	··				
SPECIAL EXPOSURE HAZARDS:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. If in a fire c heated, a pressure increase will occur and the container may rupture.						
SPECIAL PROTECTIVE EQUIPMENT FOR FIRE FIGHTERS:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. PVC boots, gloves, safety helmet and protective clothing should be worn.						
SECTION 6: ACCIDENTAL RELEASE	SE MEASURES						
ACCIDENTAL RELEASE MEASURES:	For major spills call CHEMTREC : Toll free 1-800-424-930 (ofor international call	1-703-527-3887.				
PERSONAL PRECAUTIONS:	Wear appropriate personal protective equipment recommended in SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION of this SDS. Immediately contact emergency personnel. Evacuate the area. K upwind avoiding inhalation of vapors. Clean-up should only be performed by trained personnel. People dealing with major spillages should wear full protective clothing including respiratory protection.						
ENVIRONMENTAL PRECAUTIONS:	This material may contaminate the environment without proper control and response to spills. Ensure spilled material does not come in contact with soil, waterway, drains, sewers, or other runoff that would further disperse the material. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil, or air). Sources of ignition should be kept clear.						
METHODS FOR CONTAINMENT:	Use diking or capping to control migration. Contain and absorb large spillages with a non-flammable absorbent carrier (such as vermiculite, earth, or sand). DO NOT USE combustible materials such as sawdust Shovel into open-top drums or plastic bags for further decontamination, if necessary. Remove and properly dispose of residues. Dispose of via a licensed waste disposal contractor (See SECTION 13: DISPOSAL CONSIDERATIONS) Notify applicable government authorities if release is reportable.						
METHODS FOR CLEANING UP:	CONSIDERATIONS) Notify applicable government authorities if release is reportable. Only proceed with clean up by taking the appropriate personal protection measures required and ensure surrounding area does not contain further hazards that could worsen the spill, cause migrat or cause further harm (i.e. eliminate any ignition sources). Move any non-contaminated, non-leakin containers from the spill zone if it can be done safely. Dike, dam, or further restrict and stop active leaks without posing further damage or harm to individuals, the environment, and/or structures. Contain and collect spillage. See SECTION 13: DISPOSAL CONSIDERATIONS for disposal information and SECTION 8: EXPOSURE CONTROL/ PERSONAL PROTECTION for recommended Personal Protective Equipment (PPE). Obey all local, state, and federal regulations during clean up.						

SECTION 7: HANDLING & ST	
GENERAL:	Ideal storage temperature is 60-90°F (15-32°C). Handling and storage shall be in accordance with local, state/provincial, or federal regulations.
HANDLING:	Before opening this package, read and follow warning labels on all components. Avoid contact with the product or reaction mixture. Put on appropriate personal protective equipment. Use only with adequate ventilation to ensure that the occupational exposure limit is not exceeded, use respirator when ventilation is inadequate. Avoid breathing aerosols, mists, and vapors. (See SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION for details). Do not ingest. Eating, drinking, and smoking shall be prohibited in areas where this material is handled, stored, and processed. Workers shall wash hands and face before eating, drinking, and smoking. Persons with a history of skin sensitization problems, asthma, allergies, or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Do not get in eyes, on skin, or clothing. Keep in the original container or an approved alternative made from a compatible material. Keep tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse containers.
STORAGE:	Keep container tightly closed and properly sealed when stored. When possible, store product indoors in a dry, well-ventilated area. Store in original container, away from incompatible materials, and away from food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers and use appropriate containment to avoid environmental contamination.
SECTION 8: EXPOSURE CON	ITROLS/PERSONAL PROTECTION
EXPOSURE LIMITS:	As of the latest revision of this document, no known exposure limits exist for this product. The absence of current exposure data does not relieve an employer, user, or other to determine the specific hazards and appropriate exposure protection measures in the application and use of this product. Personal, workplace, atmospheric, and/or biological monitoring may be required to determine the effectiveness of engineering, administrative, and/or other best practice control measures. These monitoring results determine the need for and type of respiratory protective equipment, if any. Refer to the appropriate local, state, and federal regulations and statutes for the most current information and for guidance in the determination of hazardous conditions and the correlating personal protective equipment.
ENGINEERING CONTROLS:	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor, or mist, use process enclosures, local exhaust ventilation, and other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
HYGIENE MEASURES:	Wash hands, forearms, and face thoroughly with plenty of soap and water after handling chemical products, before eating, smoking, and using the restroom and at the end of the working period. Appropriate engineering, administrative, and other best practice decontamination control measures must be used to isolate contaminates on clothing and to prevent unintended migration of contaminants. Handle clothing and other potentially contaminated material appropriately and in compliance with local, state, and federal regulations in the process of removing, washing/cleaning, and reuse of these potentially contaminated materials. Ensure compliant use and location of eyewash station and safety showers.
PERSONAL PROTECTIVE EQUIPMENT	NT (PPE):
EYE PROTECTION:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield.
SKIN PROTECTION:	Personal protective equipment for the body should be selected based on the task being performed, the risks involved, and should be approved by an industrial hygiene specialist before handling this product.
HANDS PROTECTION:	Chemical resistant gloves complying with applicable health and safety standards shall be worn when handling this product. Protective gloves are those made from butyl rubber, nitrile rubber, or polyvinyl alcohol. Appropriate hazard assessments in conjunction with an evaluation of the protection factors of chemical resistant gloves shall be performed to ensure the protective properties remain intact. It is noted that the time it takes to breakdown of protection factors for different glove manufacturers varies. In the case of mixtures, the protection factors of chemical resistant gloves may be impacted and deteriorate at unpredictable rates without understanding the impact of the substance and the specific protection factors of the chemical resistant gloves.
RESPIRATORY PROTECTION:	Ensure adequate ventilation. If the respirator is the sole means of protection, use a full-face supplied respirator. Use respirators and components tested and approved under appropriate government standards such as OSHA 29CFR 1910.134, NIOSH (US), or CEN (EU).
ENVIRONMENTAL EXPOSURE CONTROLS:	Dispose of raw and spent materials and wastes in compliance with all local, state, and federal regulations to prevent potential environmental contamination. Industrial air monitoring may be required to determine any potential environmental hazards to the atmosphere. This monitoring may result in the use of engineering and administrative controls such as filtering and scrubbing systems to mitigate or eliminate potential contaminants.

SECTION 9: PHYSICAL & C	HEMICAL PROPERT	TIES							
PHYSICAL STATE:	Liquid		FLASH POINT	:	>378°F (192°C)				
COLOR:	Clear	1.	AUTO-IGNITIO	ON TEMPERATURE:	Not available				
ODOR:	Amine odor		DECOMPOSIT	TION TEMPERATURE:	Not available				
ODOR THRESHOLD:	Not available		EXPLOSIVE L	IMITS:	Not explosive				
pH:	Not applicable		FLAMMABILIT	ΓY:	Not available				
WATER SOLUBILITY:	Not available		BOILING POI	NT:	Not available				
PARTITION COEFFICIENT:	Not available		BOILING RAN	IGE:	Not available				
SPECIFIC GRAVITY:	1.00±0.005 g/cc @ 77°F ((25°C)	MELTING/FRE	EZING POINT:	Not available				
VISCOSITY:	500±50 mPa.s @ 77°F (2	5°C)	VAPOR PRES	SURE:	Not available				
EVAPORATION RATE:	Not available	,	VAPOR DENS	ITY:	Not available				
VOC:	0 g/L		RELATIVE DE	NSITY:	8.3±0.05 lbs/gal				
SECTION 10: STABILITY &	REACTIVITY								
STABILITY:	Stable when handled an	d stored at	temperatures	60-90°F (15-32°C).					
INCOMPATIBILITY:	Strong reaction with acid	Strong reaction with acids and oxidizing agents.							
HAZARDOUS REACTION:	No specific data availabl	le.							
HAZARDOUS POLYMERIZATION:	Hazardous polymerization	on will not c	occur under no	ormal conditions of storage	e and use.				
CONDITIONS TO AVOID:	Avoid temperatures abov	e 100°F (38°C	C) and freezing	temperatures. Avoid mois	ture contamination in containers.				
HAZARDOUS DECOMPOSITION:	Avoid temperatures above 100°F (38°C) and freezing temperatures. Avoid moisture contamination in containers. Combustion of product will lead to oxides of nitrogen, carbon dioxide, and carbon monoxide being produced.								
SECTION 11: TOXICOLOGY									
ACUTE HEALTH EFFECTS:									
EYE CONTACT:	Not available.								
SKIN CONTACT:	Not available.								
INHALATION:	Not available.								
INGESTION:	Not available.								
ACUTE TOXICITY:									
COMPONENT NAME	CAS NUMBER	LD ₅₀ Or	ral (mg/kg)	LD ₅₀ Dermal (mg/kg)	LC ₅₀ Inhalation (mg/L/4hrs)				
Polyoxypropylenediamine	9046-10-0	2,88	85 (rat)	2,980 (rabbit)	0.37 (rat)				
Glyceryl poly (oxypropylene) triamine	64852-22-8	2,69	90 (rat)	12,500 (rabbit)	Not available				
Diethylmethylbenzenediamine	68479-98-1	73	8 (rat)	>2,000 (rabbit)	Not available				
N,N-dialkylamino-diphenylmethane	5285-60-9	1,38	80 (rat) 3,090 (rabbit)		Not available				
Dimethylthiotoluenediamine	106264-79-3	1,51	15 (rat)	>2,000 (rabbit)	Not available				
Ethyl orthoformate	122-51-0	Not a	available	Not available	Not available				
POTENTIAL CHRONIC EFFECTS:	стs:								
CHRONIC EFFECTS:	A two year study on rats showed that diethylmethylbenzenediamine caused effects in the pancreas, liver, thyroid, and eyes. There was an increase in the number of tumors in the liver and thyroid of male rats. An increase in the number of tumors in the liver and possibly mammary glands of female rats was also found. Rats given dimethylthiotoluenediamine in the diet for up to 90 days showed increased liver metabolic activity. There were kidney effects observed that were unique to male rats. These effects were similar to changes that have been observed in male rats given hydrocarbons. These effects resolved in animals allowed 30 days recovery. Rats treated for 24 months did not have microscopic alterations in any tissues compared to control animals. Tumors seen in control and treated animals were usual for the age and strain of rats.								
TARGET ORGANS:	Pancreas, liver, thyroid, and eyes.								
CARCINOGENICITY:	As of this publication, this material is not listed on the National Toxic Program (NTP) Report of Carcinogens. Please refer to the most recent information with NTP.								
MUTAGENICITY:	No known significant eff	fects or criti	ical hazards.						
TERATOGENICITY:	No known significant eff	fects or criti	ical hazards.						
FERTILITY EFFECTS:	No known significant eff	fects or criti	ical hazards.						
DEVELOPMENTAL EFFECTS:	No known significant eff	fects or criti	ical hazards.						
MEDICAL CONDITIONS AGGRAVATED BY OVER-EXPOSURE:	No known significant eff	fects or criti	ical hazards.						

SECTION 12: ECOLOGICAL INFORMATION

ENVIRONMENTAL EFFECTS:

Based on a review of the individual components, this product may be immediately harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment, and not readily biodegradable.

SECTION 13: DISPOSAL CONSIDERATION

WASTE DISPOSAL:

By-product wastes or process waste generation should be eliminated and/or minimized when possible. Do not dispose of any contaminants into sanitary sewer systems, storm drains, Publicly Owned Treatment Works (POTW), or any other municipal waste water treatment facility without written approval and agreements for processing wastes with such enterprises. Dispose of raw or unused materials, wastes, and/or by-products in accordance with all applicable local, state, and federal laws. Employ the expertise and knowledge of qualified personnel or contractors in disposal of any and all variants of this product. Ensure material containers are cleaned to the applicable standards before recycling, disposing, or reusing containers. Take special precautions to avoid any cross contamination and potential unknown effects from mixing with other substances. Refer to SECTION 8: EXPOSURE CONTROL/ PERSONAL PROTECTION of this document for personal protection requirements. Disposal to the environment or in violation of environmental protection laws and statutes must be prevented.

SECTION 14: TRANSPORT INFORMATION

Р	R	O	P	Eł	₹	SI	P	P	Ш	16	S	N	1/	71	VΙ	9

DOT:	Not regulated.
TDG:	Not regulated.
IMDG:	Not regulated.
IATA:	Not regulated.

This product could potentially contaminate aquatic and terrestrial environments if not handled in accordance with all precautions, regulations, and laws. Users, transporters, and all other applicable entities must review, follow, and apply any and all necessary precautions and procedures to eliminate and/or minimize potential hazards or risks to aquatic or terrestrial environments.

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA 8b Inventory:	All components are listed on the TSCA inventory or are exempt.
TSCA 5a (2):	No components listed.
TSCA 5e:	No components listed.
TSCA 12b:	No components listed.
Clean Air Act Section 112(b) Hazardous	No components listed.

Air Pollutants (HAPs): Clean Air Act - Ozone Depleting

This product does not contain nor is it manufactured with ozone depleting substances.

SARA 313 Form R - Reporting	COMPONENT	CAS NUMBER	CONCENTRATION	
Requirements:	Diethylmethylbenzenediamine	68479-98-1	1-10%	
SARA 311/312 hazard identification:	Immediate (acute) health hazard.			

Delayed (chronic) health hazard.

CERCLA Hazardous substances: No components listed.

STATE REGULATIONS:

Substances (ODS):

PENNSYLVANIA/NEW JERSEY/
MASSACHUSETTS - RTK:

No components listed.

California Prop 65:

This product contains less than 1% of a chemical known to the State of California to cause cancer, birth defects, or other reproductive harm, at levels which would require a warning under the statute.

CANADA

WHMIS (Canada):

WHMIS Class D-1B: Material causing immediate and serious toxic effects (toxic).

CEPA DSL:

All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

INTERNATIONAL LISTS:

Australia inventory (AICS):	All components are listed or exempted.
China inventory (IECSC):	All components are listed or exempted.
Japan inventory:	All components are listed or exempted.
Korea inventory:	All components are listed or exempted.
New Zealand inventory of Chemicals (NZIoC):	All components are listed or exempted.
Phillipines inventory (PICCS):	All components are listed or exempted.

SECTION 16: OTHER INFORMATION

NFPA & HMIS 4 Extreme 3 Serious 2 Moderate 1 Slight 0 No Hazard



National Fire Protection Association (NFPA)



FLAMMABILITY REACTIVITY SPECIAL
CDECIAL
SPECIAL
INFORMATION

Hazardous Material Information System (HMIS)

HEALTH	2
FLAMMABILITY	1
REACTIVITY	0
SPECIAL	
INFORMATION	

Note: The customer is responsible for determining the PPE code for this material. At the time of publishing, the NFPA/HMIS and the New GHS scale had opposite scales of severity. Check the most recent publications for current information.

For Your Protection:	The information and recommendations in this publication is to the best of our knowledge, reliable. The toxicity and risk characteristics of products made by SPI will necessarily differ from the toxicity and risk characteristics that occur when such products are used with other materials during a manufacturing process. The resulting risk characteristics should be determined and made known to ultimate end-users and processors. The user is responsible to comply with all applicable federal, provincial or municipal laws and regulations. SPI MAKES NO WARRANTIES OF ANY KIND, EXPRESSED OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.
Preparation Information:	This SDS supersedes ALL previous SDS versions.