

SEAMLESS SOLUTIONS FOR OVER 40 YEARS

SAFETY DATA SHEET ELASTAFLEX<sup>™</sup> ARC UB "B" Component Revised Date: 10/22/2018 Version: 8 SDS-332

SECTION 1: ID							
	DENTIFICATION						
PRODUCT NAMEELASTAFCAS NUMBERNot availaPRODUCT USEPolyureaMANUFACTURERSpecialtyADDRESS2410 104PHONE253 588FAX253 588				Coating Products, Inc. (SPI) TH ST. CT. S. STE D LAKEWOOD, WA 98499 7101 800 627 0773 7196 .LS, LEAKS, FIRE, OR EXPOSURE CALL <b>CHEMTREC</b> 9300 27 3887			
				T EMENTO			
			LABEL E	LEMENTS			
			DANG	SER			
		GH	S CLASSI	FICATION			
	CATEGORY			HAZARD STATEMENTS			
Acute toxicity oral		Category 4	H302	Harmful if swallowed.			
Acute toxicity dern	Category 4	H312	Harmful in contact with skin.				
Skin corrosion/irrit	ation	Category 1C	H314	Causes severe skin burns and eye damage.			
Acute hazard aquatic environment Category 3			H402	Harmful to aquatic life.			
Long-term hazard aquatic environment Category 2 H411 Toxic to aquatic life with long lasting effects.							
		PRECAU		STATEMENTS			
	PREVENTION						
P260	Do not breathe dust/fume/gas/mist/vapors/spray.						
P264	Wash hands thoroughly after						
P270		Do not eat, drink, or smoke when using this product.					
P273	Avoid release to the environment.						
P280	Wear protective gloves/protective clothing/eye protection/face protection.						
P301+P312	RESPONSE						
P330	IF SWALLOWED: Call a POISON CENTER or doctor/physician IF you feel unwell. Rinse mouth.						
P302+P352	IF ON SKIN: Wash with plenty of soap and water.						
P312	Call a POISON CENTER or doctor/physician if you feel unwell.						
P322	Specific measures (see section 4 on this SDS).						
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.						
	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse SKIN with water/shower.						
P363	Wash contaminated clothing before reuse.						
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.						
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.						
P310	Immediately call a POISON CENTER or doctor/physician.						
P321	Specific treatment (see section 4 on this SDS).						
P391	Collect spillage. Hazardous to the aquatic environment.						
	-		STORA	GE			
P405 Store locked up.							
P405	Store locked up.						
P501			DISPOS	SAL blicable regional, national and local laws and regulations.			



ELASTAFLEX<sup>™</sup> ARC UB "B"



Page 1 of 7

SECTION 3: COMPOSITION/INF		046 1111					
		CAS NUMBER	% WEIGHT				
Polyoxypropylenediamine	9046-10-0	30-70					
Glyceryl poly (oxypropylene) triamine	64852-22-8	20-40					
Diethylmethylbenzenediamine	68479-98-1	1-10					
*Proprietary		Not available	<u> </u>				
	ercentage (concentration) is withheld as a trade secret p	per applicable regulation	is and statutes.				
SECTION 4: FIRST AID MEASUR							
EYE:	In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water Get medical attention if symptoms occur.						
SKIN:	Wash affected areas thoroughly with soap and water.	Get medical attention if	symptoms occur.				
INHALATION:	Remove the affected individual into fresh air and keep necessary. Get medical attention if symptoms occur.	o the person calm. Assis	t in breathing if				
INGESTION:							
NOTES TO PHYSICIAN:	Symptomatic and supportive therapy as needed. Fol should be monitored for 48 hours.	lowing severe exposure	medical follow-up				
SECTION 5: FIRE FIGHTING MEA	SURES						
FLASH POINT:	>292°F (144°C).						
HAZARDS WHEN ON FIRE OR NEAR FLAME:	May produce toxic fumes of carbon dioxide and carbon monoxide when near heat source/flam When in a closed container, pressure will increase which may lead to a rupture of the container						
SUITABLE EXTINGUISHING MEDIA:	Dry chemical foam, carbon dioxide, foam, or water spray (mist/fog) to extinguish.						
	None known.						
SPECIAL EXPOSURE HAZARDS:	Promptly isolate the scene by removing all persons from fire. No action shall be taken involving any personal r heated, a pressure increase will occur and the contain	isk or without suitable tr	aining. If in a fire o				
SPECIAL PROTECTIVE EQUIPMENT FOR FIRE FIGHTERS:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. PVC boots, gloves, safety helmet and protective clothing should be worn.						
SECTION 6: ACCIDENTAL RELEA	SE MEASURES						
ACCIDENTAL RELEASE MEASURES:	For major spills call CHEMTREC: Toll free 1-800-424-5 1-703-527-3887	<b>300</b> for international ca	II				
PERSONAL PRECAUTIONS:	Wear appropriate personal protective equipment recommended in SECTION 8: EXPOSURE CONTROL/ PERSONAL PROTECTION of this SDS. Immediately contact emergency personnel. Evacuate the area. Ke upwind avoiding inhalation of vapors. Clean-up should only be performed by trained personnel. People dealing with major spillages should wear full protective clothing including respiratory protection.						
ENVIRONMENTAL PRECAUTIONS:	This material may contaminate the environment without proper control and response to spills. Ensur spilled material does not come in contact with soil, waterway, drains, sewers, or other runoff that wou further disperse the material. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil, or air). Sources of ignition should be kept clear.						
METHODS FOR CONTAINMENT:	Use diking or capping to control migration. Contain and absorb large spillages with a non-flammable absorbent carrier (such as vermiculite, earth, or sand). DO NOT USE combustible materials such as sawdus Shovel into open-top drums or plastic bags for further decontamination, if necessary. Remove and properly dispose of residues. Dispose of via a licensed waste disposal contractor (See SECTION 13: DISPOSAL CONSIDERATIONS) Notify applicable government authorities if release is reportable.						
METHODS FOR CLEANING UP:	Only proceed with clean up by taking the appropriate personal protection measures required and ensure surrounding area does not contain further hazards that could worsen the spill, cause migration or cause further harm (i.e. eliminate any ignition sources). Move any non-contaminated, non-leaking containers from the spill zone if it can be done safely. Dike, dam, or further restrict and stop active leaks without posing further damage or harm to individuals, the environment, and/or structures. Contain and collect spillage. See SECTION 13: DISPOSAL CONSIDERATIONS for disposal informatior and SECTION 8: EXPOSURE CONTROL/ PERSONAL PROTECTION for recommended Personal Protective Equipment (PPE). Obey all local, state, and federal regulations during clean up.						

SECTION 7: HANDLING & STOR	AGE				
GENERAL:	Ideal storage temperature is 60-90°F (15-32°C). Handling and storage shall be in accordance with local, state/provincial, or federal regulations.				
HANDLING:	Before opening this package, read and follow warning labels on all components. Avoid contact with the product or reaction mixture. Put on appropriate personal protective equipment. Use only with adequate ventilation to ensure that the occupational exposure limit is not exceeded, use respirator when ventilation is inadequate. Avoid breathing aerosols, mists, and vapors. (See SECTION 8: EXPOSURE CONTROL/ PERSONAL PROTECTION for details). Do not ingest. Eating, drinking, and smoking shall be prohibited in areas where this material is handled, stored, and processed. Workers shall wash hands and face before eating, drinking, and smoking. Persons with a history of skin sensitization problems, asthma, allergies, or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Do not get in eyes, on skin, or clothing. Keep in the original container or an approved alternative made from a compatible material. Keep tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse containers.				
STORAGE:	Keep container tightly closed and properly sealed when stored. When possible, store product indoors in a dry, well-ventilated area. Store in original container, away from incompatible materials, and away from food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers and use appropriate containment to avoid environmental contamination.				
SECTION 8: EXPOSURE CONTR	OLS/PERSONAL PROTECTION				
EXPOSURE LIMITS:	As of the latest revision of this document, no known exposure limits exist for this product. The absence of current exposure data does not relieve an employer, user, or other to determine the specific hazards and appropriate exposure protection measures in the application and use of this product. Personal, workplace, atmospheric, and/or biological monitoring may be required to determine the effectiveness of engineering, administrative, and/or other best practice control measures. These monitoring results determine the need for and type of respiratory protective equipment, if any. Refer to the appropriate local, state, and federal regulations and statutes for the most current information and for guidance in the determination of hazardous conditions and the correlating personal protective equipment.				
ENGINEERING CONTROLS:	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor, or mist, use process enclosures, local exhaust ventilation, and other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.				
HYGIENE MEASURES:	Wash hands, forearms, and face thoroughly with plenty of soap and water after handling chemical products, before eating, smoking, and using the restroom and at the end of the working period. Appropriate engineering, administrative, and other best practice decontamination control measures must be used to isolate contaminates on clothing and to prevent unintended migration of contaminants. Handle clothing and other potentially contaminated material appropriately and in compliance with local, state, and federal regulations in the process of removing, washing/cleaning, and reuse of these potentially contaminated materials. Ensure compliant use and location of eyewash station and safety showers.				
PERSONAL PROTECTIVE EQUIPMENT	PPE):				
EYE PROTECTION:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield.				
SKIN PROTECTION:	Personal protective equipment for the body should be selected based on the task being performed, the risks involved, and should be approved by an industrial hygiene specialist before handling this product.				
HANDS PROTECTION:	Chemical resistant gloves complying with applicable health and safety standards shall be worn when handling this product. Protective gloves are those made from butyl rubber, nitrile rubber, or polyvinyl alcohol. Appropriate hazard assessments in conjunction with an evaluation of the protection factors of chemical resistant gloves shall be performed to ensure the protective properties remain intact. It is noted that the time it takes to breakdown of protection factors of chemical resistant gloves manufacturers varies. In the case of mixtures, the protection factors of chemical resistant gloves may be impacted and deteriorate at unpredictable rates without understanding the impact of the substance and the specific protection factors of the chemical resistant gloves.				
RESPIRATORY PROTECTION:	Ensure adequate ventilation. If the respirator is the sole means of protection, use a full-face supplied respirator. Use respirators and components tested and approved under appropriate government standards such as OSHA 29CFR 1910.134, NIOSH (US), or CEN (EU).				
ENVIRONMENTAL EXPOSURE CONTROLS:	Dispose of raw and spent materials and wastes in compliance with all local, state, and federal regulations to prevent potential environmental contamination. Industrial air monitoring may be required to determine any potential environmental hazards to the atmosphere. This monitoring may result in the use of engineering and administrative controls such as filtering and scrubbing systems to mitigate or eliminate potential contaminants.				

SECTION 9: PHYSICAL & C		TIES					
PHYSICAL STATE:	Liquid	FLAS		:	>292°F (144°C)		
COLOR:	Brown	AUTO	-IGNITIC	ON TEMPERATURE:	Not available		
ODOR:	Amine odor	DECO	MPOSI	TION TEMPERATURE:	Not available		
ODOR THRESHOLD:	Not available	EXPLO	OSIVE L	IMITS:	Not explosive		
pH:	Not applicable	FLAM	MABILI	ΓY:	Not available		
WATER SOLUBILITY:	Not available	BOILI	NG POI	NT:	Not available		
PARTITION COEFFICIENT:	Not available	BOILI	NG RAN	GE:	Not available		
SPECIFIC GRAVITY:	1.00±0.005 g/cc @ 77°F (	25°C) MELTI	NG/FRE	EZING POINT:	Not available		
VISCOSITY:	400±25 mPa.s @ 77°F (2	5°C) <b>VAPO</b>	R PRES	SURE:	Not available		
EVAPORATION RATE:	Not available	VAPO	R DENS	ITY:	Not available		
VOC:	0 g/L	RELAT		NSITY:	8.3±0.05 lbs/gal		
SECTION 10: STABILITY &	REACTIVITY						
STABILITY:	Stable when handled an	d stored at tempe	eratures	60-90°F (15-32°C).			
INCOMPATIBILITY:	Strong reaction with acid	ds and oxidizing a	igents.				
HAZARDOUS REACTION:	No specific data availabl	e.					
HAZARDOUS POLYMERIZATION:	Hazardous polymerizatio	on will not occur u	under no	rmal conditions of storage	e and use.		
CONDITIONS TO AVOID:	Avoid temperatures above 100°F (38°C) and freezing temperatures. Avoid moisture contamination in contai						
HAZARDOUS DECOMPOSITION:	Combustion of product w	ill lead to oxides of	f nitroger	n, carbon dioxide, and carbo	on monoxide being produced.		
SECTION 11: TOXICOLOGY	INFORMATION						
ACUTE HEALTH EFFECTS:							
EYE CONTACT:	Not available.						
SKIN CONTACT:	Not available.						
INHALATION:	Not available.						
INGESTION:	Not available.						
ACUTE TOXICITY:							
COMPONENT NAME	CAS NUMBER	LD <sub>50</sub> Oral (mg	J/kg)	LD <sub>50</sub> Dermal (mg/kg)	LC <sub>50</sub> Inhalation (mg/L/4hrs)		
Polyoxypropylenediamine	9046-10-0	2,885 (rat	)	2,980 (rabbit)	0.37 (rat)		
Glyceryl poly (oxypropylene) triamine	64852-22-8	2,690 (rat	)	12,500 (rabbit)	Not available		
Diethylmethylbenzenediamine	68479-98-1	738 (rat)	38 (rat) >2,000 (rabbit)		Not available		
POTENTIAL CHRONIC EFFECTS:							
CHRONIC EFFECTS:	FECTS: A two year study on rats showed that diethylmethylbenzenediamine caused effects in the pancreas, liver, thyroid, and eyes. There was an increase in the number of tumors in the liver and thyroid of male rats. An increase in the number of tumors in the liver and possibly mammary glands of female rats was also found.						
TARGET ORGANS:	Pancreas, liver, thyroid, and eyes.						
CARCINOGENICITY:	As of this publication, this material is not listed on the National Toxic Program (NTP) Report of Carcinogens. Please refer to the most recent information with NTP.						
MUTAGENICITY:	No known significant effects or critical hazards.						
TERATOGENICITY:	No known significant eff	ects or critical ha	zards.				
FERTILITY EFFECTS:	No known significant eff	ects or critical ha	zards.				
DEVELOPMENTAL EFFECTS:	No known significant eff	ects or critical ha	zards.				
MEDICAL CONDITIONS AGGRAVATED BY OVER-EXPOSURE:	No known significant ef	ects or critical ha	zards.				

ENVIRONMENTAL EFFECTS:	Based on a rev	ased on a review of the individual components, this product may be immediately harmful to aquatic organisms,						
may cause long-term adverse effects in the aquatic environment, and not readily biodegradable.				, and not readily biodegradable.				
SECTION 13: DISPOSAL CO	NSIDERATION							
WASTE DISPOSAL:	Do not dispos Works (POTW agreements for and/or by-pro and knowledg Ensure materi containers. Ta mixing with ot of this docum	By-product wastes or process waste generation should be eliminated and/or minimized when possible. Do not dispose of any contaminants into sanitary sewer systems, storm drains, Publicly Owned Treatment Works (POTW), or any other municipal waste water treatment facility without written approval and agreements for processing wastes with such enterprises. Dispose of raw or unused materials, wastes, and/or by-products in accordance with all applicable local, state, and federal laws. Employ the expertise and knowledge of qualified personnel or contractors in disposal of any and all variants of this product. Ensure material containers are cleaned to the applicable standards before recycling, disposing, or reusing containers. Take special precautions to avoid any cross contamination and potential unknown effects from mixing with other substances. Refer to SECTION 8: EXPOSURE CONTROL/ PERSONAL PROTECTION of this document for personal protection requirements. Disposal to the environment or in violation of environmental protection laws and statutes must be prevented.						
SECTION 14: TRANSPORT I	NFORMATION							
PROPER SHIPPING NAME								
DOT:	Amines, liqui	Amines, liquid, corrosive, n.o.s. (Polyoxypropylendiamine)						
TDG:	Amines, liqui	Amines, liquid, corrosive, n.o.s. (Polyoxypropylendiamine)						
IMDG:	Amines, liqui	Amines, liquid, corrosive, n.o.s. (Polyoxypropylendiamine)						
IATA:	Amines, liqui	Amines, liquid, corrosive, n.o.s. (Polyoxypropylendiamine)						
This product could potentially conta and laws. Users, transporters, and a procedures to eliminate and/or mini	Il other applicable	entities must re	eview, fo	llow, and apply any a	ccordance with all precautions, regulation nd all necessary precautions and nents.			
REGULATORY INFORMATION	UN NUMBER	CLASSES	PG*	LABEL	ADDITIONAL INFORMATION			
DOT Classification	UN2735	8	111	CORROSIVE 8	None			
TDG Classification	UN2735	8		CORROSIVE	None			

				8	
TDG Classification	UN2735	8	111	CORROSIVE 8	None
IMDG Classification	UN2735	8	111	CORROSIVE 8	<u>Emergency</u> <u>schedules (EmS)</u> F-A, S-B
IATA-DGR Classification	UN2735	8	111	CORROSIVE 8	Passenger and Cargo Aircraft Quantity limitation: 5 L Packaging Instructions: 852 Cargo Aircraft Only Quantity limitation: 60 L Packaging Instructions: 856
*PG: Packaging group					

SECTION 15: REGULATORY INF	ORMATION					
U.S. FEDERAL REGULATIONS						
TSCA 8b Inventory:	All components are listed on the TSCA inventory or are exempt.					
TSCA 5a (2):	No components listed.					
TSCA 5e:	No components listed.					
TSCA 12b:	No components listed.					
Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs):	No components listed.					
Clean Air Act - Ozone Depleting Substances (ODS):	This product does not contain nor is i	t manufactured with ozone	depleting substances.			
SARA 313 Form R - Reporting	COMPONENT	CAS NUMBER	CONCENTRATION			
Requirements:	Diethylmethylbenzenediamine	68479-98-1	1-10%			
SARA 311/312 hazard identification:	Immediate (acute) health hazard. Delayed (chronic) health hazard.					
CERCLA Hazardous substances:	No components listed.					
STATE REGULATIONS:						
PENNSYLVANIA/NEW JERSEY/ MASSACHUSETTS - RTK:	No components listed.					
California Prop 65:	This product contains no listed substances known to the State of California to cause cancer, birth defects, or other reproductive harm, at levels which would require a warning under the statute.					
CANADA						
WHMIS (Canada): WHMIS Class D-1B: Material causing immediate and serious toxic effects (toxic).   WHMIS Class E: Corrosive.						
CEPA DSL:	All components are listed or exempted.					
This product has been classified in acco the information required by the Controll		Controlled Products Regu	lations and the SDS contains all			
INTERNATIONAL LISTS:						
Australia inventory (AICS):	All components are listed or exempted.					
China inventory (IECSC):	All components are listed or exempted.					
Japan inventory:	All components are listed or exempted.					
Korea inventory:	All components are listed or exempted.					
New Zealand inventory of Chemicals (NZIoC):	All components are listed or exempted.					
Phillipines inventory (PICCS):	All components are listed or exempte	ed.				

## **SECTION 16: OTHER INFORMATION**



## Note: The customer is responsible for determining the PPE code for this material. At the time of publishing, the NFPA/HMIS and the New GHS scale had opposite scales of severity. Check the most recent publications for current information.

For Your Protection:	The information and recommendations in this publication is to the best of our knowledge, reliable. The toxicity and risk characteristics of products made by SPI will necessarily differ from the toxicity and risk characteristics that occur when such products are used with other materials during a manufacturing process. The resulting risk characteristics should be determined and made known to ultimate end-users and processors. The user is responsible to comply with all applicable federal, provincial or municipal laws and regulations. SPI MAKES NO WARRANTIES OF ANY KIND, EXPRESSED OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.
Preparation Information:	This SDS supersedes ALL previous SDS versions.

3

1

0