

SAFETY DATA SHEET

DRAGONSHIELD-HT® ERC "B" Component Revised Date: 11/13/2019

Version: 10 SDS-244

SECTION 1: IDENTIFICATION

PRODUCT NAME
CAS NUMBER
PRODUCT USE
MANUFACTURER
ADDRESS
PHONE
FAX
EMERGENCY CONTACT
TOLL FREE

INTERNATIONAL

FAX

DRAGONSHIELD-HT® ERC"B" Component

Not available Polyurea Coating Specialty Products, Inc. (SPI)

2410 104TH ST. CT. S. STE D LAKEWOOD, WA 98499

253 588 7101 800 627 0773

253 588 7196

FOR SPILLS, LEAKS, FIRE, OR EXPOSURE CALL CHEMTREC

800 424 9300 +1 703 527 3887 913 321 1490

SECTION 2: HAZARDS IDENTIFICATION

GHS LABEL ELEMENTS

GHS PICTOGRAM







DANGER

GHS CLASSIFICATION					
CATEGORY HAZARD STATEMENTS					
Acute toxicity oral	Category 4	H302	Harmful if swallowed.		
Acute toxicity dermal	Category 4	H312	Harmful in contact with skin.		
Skin corrosion/irritation	Category 1C	H314	Causes severe skin burns and eye damage.		
Acute hazard aquatic environment	Category 3	H402	Harmful to aquatic life.		
Long-term hazard aquatic environment	Category 2	H411	Toxic to aquatic life with long lasting effects.		

PRECAUTIONARY STATEMENTS			
	PREVENTION		
P260	Do not breathe dust/fume/gas/mist/vapors/spray.		
P264	Wash hands thoroughly after handling.		
P270	Do not eat, drink, or smoke when using this product.		
P273	Avoid release to the environment.		
P280	Wear protective gloves/protective clothing/eye protection/face protection.		
	RESPONSE		
P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician IF you feel unwell.		
P330	Rinse mouth.		
P302+P352	IF ON SKIN: Wash with plenty of soap and water.		
P312	Call a POISON CENTER or doctor/physician if you feel unwell.		
P322	Specific measures (see section 4 on this SDS).		
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.		
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse SKIN with water/shower.		
P363	Wash contaminated clothing before reuse.		
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.		
P310	Immediately call a POISON CENTER or doctor/physician.		
P321	Specific treatment (see section 4 on this SDS).		
P391	Collect spillage. Hazardous to the aquatic environment.		
STORAGE			
P405	Store locked up.		
	DISPOSAL		
P501	Dispose of contents/container in accordance with applicable regional, national and local laws and regulations.		

SECTION 3: COMPOSITION/INFO		CAS NUMBER	% WEIGHT	
Polyoxypropylenediamine		9046-10-0	50-90	
Diethylmethylbenzenediamine		68479-98-1	20-40	
Silane		Not available	1-10	
Glyceryl poly (oxypropylene) triamine		64852-22-8	1-10	
SECTION 4: FIRST AID MEASUR	ES CONTRACTOR OF THE			
EYE:	In case of contact with the eyes, rinse immediately for Get medical attention if symptoms occur.	at least 15 minutes with	plenty of water.	
SKIN:	Wash affected areas thoroughly with soap and water.	Get medical attention if s	symptoms occur.	
INHALATION:	Remove the affected individual into fresh air and keep necessary. Get medical attention if symptoms occur.	the person calm. Assist	in breathing if	
INGESTION:	Rinse mouth and then drink plenty of water. Do not inc give anything by mouth if the victim is unconscious or if symptoms occur.	duce vomiting. Never ind having convulsions. Get	uce vomiting or medical attention	
NOTES TO PHYSICIAN:	Symptomatic and supportive therapy as needed. Followhould be monitored for 48 hours.	owing severe exposure,	medical follow-up	
SECTION 5: FIRE FIGHTING MEA	SURES			
FLASH POINT:	Not available.			
HAZARDS WHEN ON FIRE OR NEAR FLAME:	May produce toxic fumes of carbon dioxide and carbo When in a closed container, pressure will increase whi			
SUITABLE EXTINGUISHING MEDIA:	Dry chemical foam, carbon dioxide, foam, or water spray (mist/fog) to extinguish.			
UNSUITABLE EXTINGUISHING MEDIA:	None known.			
SPECIAL EXPOSURE HAZARDS:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. If in a fire or heated, a pressure increase will occur and the container may rupture.			
SPECIAL PROTECTIVE EQUIPMENT FOR FIRE FIGHTERS:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. PVC boots, gloves, safety helmet and protective clothing should be worn.			
SECTION 6: ACCIDENTAL RELEA	SE MEASURES			
ACCIDENTAL RELEASE MEASURES:	For major spills call CHEMTREC : Toll free 1-800-424-9 1-703-527-3887 .	300 for international cal	I	
PERSONAL PRECAUTIONS:	Wear appropriate personal protective equipment recommen PERSONAL PROTECTION of this SDS. Immediately contact upwind avoiding inhalation of vapors. Clean-up should only I dealing with major spillages should wear full protective clothing.	emergency personnel. Eva- be performed by trained per	cuate the area. Keep rsonnel. People	
ENVIRONMENTAL PRECAUTIONS:	This material may contaminate the environment without p spilled material does not come in contact with soil, water further disperse the material. Inform the relevant authorit pollution (sewers, waterways, soil, or air). Sources of ignit	way, drains, sewers, or othe ies if the product has caus	er runoff that would	
METHODS FOR CONTAINMENT:	Use diking or capping to control migration. Contain and absorb large spillages with a non-flammable absorbent carrier (such as vermiculite, earth, or sand). DO NOT USE combustible materials such as sawdust. Shovel into open-top drums or plastic bags for further decontamination, if necessary. Remove and properly dispose of residues. Dispose of via a licensed waste disposal contractor (See SECTION 13: DISPOSAL CONSIDERATIONS) Notify applicable government authorities if release is reportable.			
METHODS FOR CLEANING UP:	Only proceed with clean up by taking the appropriate per ensure surrounding area does not contain further hazards or cause further harm (i.e. eliminate any ignition sources). containers from the spill zone if it can be done safely. Dik leaks without posing further damage or harm to individua Contain and collect spillage. See SECTION 13: DISPOSAL and SECTION 8: EXPOSURE CONTROL/ PERSONAL PROPROTECTION 13: DISPOSAL PROPROTECTION 14: DISPOSAL PROPROTECTION 15: DISPOSAL PROPROTECTION 16: EXPOSURE CONTROL/ PERSONAL PROPROTECTION 16: DISPOSAL PROPROTECTION 16:	s that could worsen the sp Move any non-contamina e, dam, or further restrict a ls, the environment, and/o _ CONSIDERATIONS for do DTECTION for recommend	ill, cause migration, ated, non-leaking and stop active or structures. isposal information ded Personal	

SECTION 7: HANDLING & STOR	AGE
GENERAL:	Ideal storage temperature is 60-90°F (15-32°C). Handling and storage shall be in accordance with local, state/provincial, or federal regulations.
HANDLING:	Before opening this package, read and follow warning labels on all components. Avoid contact with the product or reaction mixture. Put on appropriate personal protective equipment. Use only with adequate ventilation to ensure that the occupational exposure limit is not exceeded, use respirator when ventilation is inadequate. Avoid breathing aerosols, mists, and vapors. (See SECTION 8: EXPOSURE CONTROL/ PERSONAL PROTECTION for details). Do not ingest. Eating, drinking, and smoking shall be prohibited in areas where this material is handled, stored, and processed. Workers shall wash hands and face before eating, drinking, and smoking. Persons with a history of skin sensitization problems, asthma, allergies, or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Do not get in eyes, on skin, or clothing. Keep in the original container or an approved alternative made from a compatible material. Keep tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse containers.
STORAGE:	Keep container tightly closed and properly sealed when stored. When possible, store product indoors in a dry, well-ventilated area. Store in original container, away from incompatible materials, and away from food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers and use appropriate containment to avoid environmental contamination.
SECTION 8: EXPOSURE CONTR	ROLS/PERSONAL PROTECTION
EXPOSURE LIMITS:	As of the latest revision of this document, no known exposure limits exist for this product. The absence of current exposure data does not relieve an employer, user, or other to determine the specific hazards and appropriate exposure protection measures in the application and use of this product. Personal, workplace, atmospheric, and/or biological monitoring may be required to determine the effectiveness of engineering, administrative, and/or other best practice control measures. These monitoring results determine the need for and type of respiratory protective equipment, if any. Refer to the appropriate local, state, and federal regulations and statutes for the most current information and for guidance in the determination of hazardous conditions and the correlating personal protective equipment.
ENGINEERING CONTROLS:	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor, or mist, use process enclosures, local exhaust ventilation, and other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
HYGIENE MEASURES:	Wash hands, forearms, and face thoroughly with plenty of soap and water after handling chemical products, before eating, smoking, and using the restroom and at the end of the working period. Appropriate engineering, administrative, and other best practice decontamination control measures must be used to isolate contaminates on clothing and to prevent unintended migration of contaminants. Handle clothing and other potentially contaminated material appropriately and in compliance with local, state, and federal regulations in the process of removing, washing/cleaning, and reuse of these potentially contaminated materials. Ensure compliant use and location of eyewash station and safety showers.
PERSONAL PROTECTIVE EQUIPMENT	(PPE):
EYE PROTECTION:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield.
SKIN PROTECTION:	Personal protective equipment for the body should be selected based on the task being performed, the risks involved, and should be approved by an industrial hygiene specialist before handling this product.
HANDS PROTECTION:	Chemical resistant gloves complying with applicable health and safety standards shall be worn when handling this product. Protective gloves are those made from butyl rubber, nitrile rubber, or polyvinyl alcohol. Appropriate hazard assessments in conjunction with an evaluation of the protection factors of chemical resistant gloves shall be performed to ensure the protective properties remain intact. It is noted that the time it takes to breakdown of protection factors for different glove manufacturers varies. In the case of mixtures, the protection factors of chemical resistant gloves may be impacted and deteriorate at unpredictable rates without understanding the impact of the substance and the specific protection factors of the chemical resistant gloves.
RESPIRATORY PROTECTION:	Ensure adequate ventilation. If the respirator is the sole means of protection, use a full-face supplied respirator. Use respirators and components tested and approved under appropriate government standards such as OSHA 29CFR 1910.134, NIOSH (US), or CEN (EU).
ENVIRONMENTAL EXPOSURE CONTROLS:	Dispose of raw and spent materials and wastes in compliance with all local, state, and federal regulations to prevent potential environmental contamination. Industrial air monitoring may be required to determine any potential environmental hazards to the atmosphere. This monitoring may result in the use of engineering and administrative controls such as filtering and scrubbing systems to mitigate or eliminate potential contaminants.

SECTION 9: PHYSICAL & C	HEMICAL PROPERT	ΓIES				
PHYSICAL STATE:	Liquid		FLASH POINT	:	352°F (178°C)	
COLOR:	Clear		AUTO-IGNITIO	ON TEMPERATURE:	Not available	
ODOR:	Amine odor		DECOMPOSIT	TION TEMPERATURE:	Not available	
ODOR THRESHOLD:	Not available		EXPLOSIVE L	IMITS:	Not explosive	
pH:	Not applicable		FLAMMABILI	ΓY:	Not available	
WATER SOLUBILITY:	Not available		BOILING POI	NT:	Not available	
PARTITION COEFFICIENT:	Not available		BOILING RAN	IGE:	Not available	
SPECIFIC GRAVITY:	1.00±0.005 g/cc @ 77°F (25°C)	MELTING/FRE	EZING POINT:	Not available	
VISCOSITY:	275±75 mPa.s @ 77°F (25	5°C)	VAPOR PRES	SURE:	Not available	
EVAPORATION RATE:	Not available		VAPOR DENS	SITY:	Not available	
VOC:	0 g/L		RELATIVE DE	NSITY:	8.4±0.05 lbs/gal	
SECTION 10: STABILITY &	REACTIVITY					
STABILITY:	Stable when handled an	d stored a	t temperatures	60-90°F (15-32°C).		
INCOMPATIBILITY:	Strong reaction with acid	ds and oxid	dizing agents.			
HAZARDOUS REACTION:	No specific data availabl	le.				
HAZARDOUS POLYMERIZATION:	Hazardous polymerizatio	on will not	occur under no	ormal conditions of storage	e and use.	
CONDITIONS TO AVOID:	Avoid temperatures above	e 100°F (38	S°C) and freezing	temperatures. Avoid moist	ure contamination in containers.	
HAZARDOUS DECOMPOSITION:	Combustion of product will lead to oxides of nitrogen, carbon dioxide, and carbon monoxide being produced.					
SECTION 11: TOXICOLOGY	Y INFORMATION					
ACUTE HEALTH EFFECTS:						
EYE CONTACT:	Not available.					
SKIN CONTACT:	Not available.					
INHALATION:	Not available.					
INGESTION:	Not available.					
ACUTE TOXICITY:						
COMPONENT NAME	CAS NUMBER	LD ₅₀ C	ral (mg/kg)	LD ₅₀ Dermal (mg/kg)	LC ₅₀ Inhalation (mg/L/4hrs)	
Polyoxypropylenediamine	9046-10-0	2,8	385 (rat)	2,980 (rabbit)	0.37 (rat)	
Diethylmethylbenzenediamine	68479-98-1	7:	38 (rat)	>2,000 (rabbit)	Not available	
Silane	*Proprietary	24	,182 (rat)	4,248 (rabbit)	Not available	
Glyceryl poly (oxypropylene) triamine	64852-22-8	2,6	690 (rat)	12,500(rabbit)	Not available	
POTENTIAL CHRONIC EFFECTS:						
CHRONIC EFFECTS:	C EFFECTS: A two year study on rats showed that diethylmethylbenzenediamine caused effects in the pancreas, liver, thyroid, and eyes. There was an increase in the number of tumors in the liver and thyroid of male rats. An increase in the number of tumors in the liver and possibly mammary glands of female rats was also found.					
TARGET ORGANS:	Pancreas, liver, thyroid, and eyes.					
CARCINOGENICITY:	As of this publication, this material is not listed on the National Toxic Program (NTP) Report of Carcinogens. Please refer to the most recent information with NTP.					
MUTAGENICITY:	No known significant effects or critical hazards.					
TERATOGENICITY:	No known significant effects or critical hazards.					
FERTILITY EFFECTS:	No known significant effects or critical hazards.					
DEVELOPMENTAL EFFECTS:	No known significant effects or critical hazards.					
MEDICAL CONDITIONS AGGRAVATED BY OVER-EXPOSURE:	No known significant effects or critical hazards.					

SECTION 12: ECOLOGICAL INFORMATION

ENVIRONMENTAL EFFECTS:

Based on a review of the individual components, this product may be immediately harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment, and not readily biodegradable.

SECTION 13: DISPOSAL CONSIDERATION

WASTE DISPOSAL:

By-product wastes or process waste generation should be eliminated and/or minimized when possible. Do not dispose of any contaminants into sanitary sewer systems, storm drains, Publicly Owned Treatment Works (POTW), or any other municipal waste water treatment facility without written approval and agreements for processing wastes with such enterprises. Dispose of raw or unused materials, wastes, and/or by-products in accordance with all applicable local, state, and federal laws. Employ the expertise and knowledge of qualified personnel or contractors in disposal of any and all variants of this product. Ensure material containers are cleaned to the applicable standards before recycling, disposing, or reusing containers. Take special precautions to avoid any cross contamination and potential unknown effects from mixing with other substances. Refer to SECTION 8: EXPOSURE CONTROL/ PERSONAL PROTECTION of this document for personal protection requirements. Disposal to the environment or in violation of environmental protection laws and statutes must be prevented.

SECTION 14: TRANSPORT INFORMATION

PROPER SHIPPING NAME		
DOT:	Not regulated	
TDG:	Not regulated	
IMDG:	Not regulated	
IATA:	Not regulated	

This product could potentially contaminate aquatic and terrestrial environments if not handled in accordance with all precautions, regulations, and laws. Users, transporters, and all other applicable entities must review, follow, and apply any and all necessary precautions and procedures to eliminate and/or minimize potential hazards or risks to aquatic or terrestrial environments.

DOT Classification UN2735 8 III CORROSIVE None IMDG Classification UN2735 8 III Emergency schedules (EmS) F-A, S-B Passenger and Cargo Aircraft Quantity limitation: 5 L Packaging Instructions: 852 Cargo Aircraft Only Quantity limitation: 60 L Packaging Packaging Unstructions: 60 L Packaging Packaging United Descriptions: 60 L Packaging Packaging United Descriptions: 60 L Packaging Packaging United Descriptions: 60 L	REGULATORY INFORMATION	UN NUMBER	CLASSES	PG*	LABEL	ADDITIONAL INFORMATION
IMDG Classification UN2735 8 III CORROSIVE Schedules (EmS) F-A, S-B Passenger and Cargo Aircraft Quantity limitation: 5 L Packaging Instructions: 852 Cargo Aircraft Only Quantity limitation: 60 L Packaging Passenger and Cargo Aircraft Only Quantity limitation: 60 L Packaging	DOT Classification	UN2735	8	III		None
Passenger and Cargo Aircraft Quantity limitation: 5 L Packaging Instructions: 852 Cargo Aircraft Only Quantity limitation: 60 L Packaging Passenger and Packaging Passenger and	TDG Classification	UN2735	8	III	CORROSIVE	None
IATA-DGR Classification UN2735 8 III Cargo Áircraft Quantity limitation: 5 L Packaging Instructions: 852 Cargo Aircraft Only Quantity limitation: 60 L Packaging	IMDG Classification	UN2735	8	III	CORROSIVE	Emergency schedules (EmS) F-A, S-B
Instructions: 856	IATA-DGR Classification	UN2735	8	III	CORROSIVE 8	Cargo Aircraft Quantity limitation: 5 L Packaging Instructions: 852 Cargo Aircraft Only Quantity limitation: 60 L

SECTION 15: REGULATORY INFO	ORMATION			
U.S. FEDERAL REGULATIONS				
TSCA 8b Inventory:	All components are listed on the T	All components are listed on the TSCA inventory or are exempt.		
TSCA 5a (2):	No components listed.			
TSCA 5e:	No components listed.			
TSCA 12b:	No components listed.			
Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs):	No components listed.			
Clean Air Act - Ozone Depleting Substances (ODS):	This product does not contain nor	is it manufactured with ozone	e depleting substances.	
SARA 313 Form R - Reporting	COMPONENT	CAS NUMBER	CONCENTRATION	
Requirements:	Diethylmethylbenzenediamine	68479-98-1	20-40%	
SARA 311/312 hazard identification:	Immediate (acute) health hazard. Delayed (chronic) health hazard.			
CERCLA Hazardous substances:	No components listed.			
STATE REGULATIONS:				
PENNSYLVANIA/NEW JERSEY/ MASSACHUSETTS - RTK:	No components listed.			
California Prop 65:	This product contains no listed substances known to the State of California to cause cancer, birth defects, or other reproductive harm, at levels which would require a warning under the statute.			
CANADA				
WHMIS (Canada):	WHMIS Class D-1B: Material causin WHMIS Class E: Corrosive.	g immediate and serious tox	ic effects (toxic).	
CEPA DSL:	All components are listed or exempted.			
This product has been classified in acco the information required by the Controll		he Controlled Products Reg	ulations and the SDS contains all	
INTERNATIONAL LISTS:				
Australia inventory (AICS):	All components are listed or exemp	oted.		
China inventory (IECSC):	All components are listed or exempted.			
Japan inventory:	All components are listed or exempted.			
Korea inventory:	All components are listed or exempted.			
New Zealand inventory of Chemicals (NZIoC):	All components are listed or exempted.			
Phillipines inventory (PICCS):	All components are listed or exemp	oted.		

SECTION 16: OTHER INFORMATION

NFPA & HMIS		
4	Extreme	
3	Serious	
2	Moderate	
1	Slight	
0	No Hazard	



National Fire Protection Association (NFPA)



HEALTH
FLAMMABILITY
REACTIVITY
SPECIAL
INFORMATION

Hazardous Material Information System (HMIS)

HEALTH	3
FLAMMABILITY	1
REACTIVITY	0
SPECIAL	
INFORMATION	

Note: The customer is responsible for determining the PPE code for this material. At the time of publishing, the NFPA/HMIS and the New GHS scale had opposite scales of severity. Check the most recent publications for current information.

For Your Protection:	The information and recommendations in this publication is to the best of our knowledge, reliable. The toxicity and risk characteristics of products made by SPI will necessarily differ from the toxicity and risk characteristics that occur when such products are used with other materials during a manufacturing process. The resulting risk characteristics should be determined and made known to ultimate end-users and processors. The user is responsible to comply with all applicable federal, provincial or municipal laws and regulations. SPI MAKES NO WARRANTIES OF ANY KIND, EXPRESSED OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.
Preparation Information:	This SDS supersedes ALL previous SDS versions.