

SAFETY DATA SHEET

ULTRA BOND™ HT FC "B" Component Revised Date: 11/30/2019

Version: 8 SDS-168

SECTION 1: IDENTIFICATION

PRODUCT NAME
CAS NUMBER
PRODUCT USE
MANUFACTURER
ADDRESS
PHONE
FAX
EMERGENCY CONTACT
TOLL FREE

INTERNATIONAL

FAX

ULTRA BOND™ HT FC "B" Component

Not available Polyurea Coating Specialty Products, Inc. (SPI)

2410 104TH ST. CT. S. STE D LAKEWOOD, WA 98499

253 588 7101 800 627 0773

253 588 7196

FOR SPILLS, LEAKS, FIRE, OR EXPOSURE CALL CHEMTREC

800 424 9300 +1 703 527 3887 913 <u>321 1490</u>

SECTION 2: HAZARDS IDENTIFICATION

GHS LABEL ELEMENTS

GHS PICTOGRAM







DANGER

GHS CLASSIFICATION					
CATEGORY			HAZARD STATEMENTS		
Acute toxicity oral	Category 4	H302	Harmful if swallowed.		
Skin corrosion/irritation	Category 1C	H314	Causes severe skin burns and eye damage.		
Eye corrosion/irritation	Category 1	H318	Causes serious eye damage.		
Acute hazard aquatic environment	Category A3	H402	Harmful to aquatic life.		
Long-term hazard aquatic environment	Category 2	H411	Toxic to aquatic life with long lasting effects.		

	PRECAUTIONARY STATEMENTS			
	PREVENTION			
P260	Do not breathe dust/fume/gas/mist/vapors/spray.			
P264	Wash hands thoroughly after handling.			
P270	Do not eat, drink, or smoke when using this product.			
P273	Avoid release to the environment.			
P280	Wear protective gloves/protective clothing/eye protection/face protection.			
	RESPONSE			
P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician IF you feel unwell.			
P330	Rinse mouth.			
P302+P352	IF ON SKIN: Wash with plenty of soap and water.			
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.			
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse SKIN with water/shower.			
P363	Wash contaminated clothing before reuse.			
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.			
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.			
P310	Immediately call a POISON CENTER or doctor/physician.			
P321	Specific treatment (see section 4 on this SDS).			
	STORAGE			
P405	Store locked up.			
	DISPOSAL			
P501	Dispose of contents/container in accordance with applicable regional, national and local laws and regulations.			

SECTION 3: COMPOSITION/INFO	DRMATION ON INGREDIENTS				
CHEMICAL NAME		CAS NUMBER	% WEIGHT		
Polyoxypropylenediamine 9046-10-0					
Diethylmethylbenzenediamine	68479-98-1 20-30				
Glyceryl poly (oxypropylene) triamine		64852-22-8	1-5		
SECTION 4: FIRST AID MEASURI	ES CONTRACTOR OF THE				
EYE:	In case of contact with the eyes, rinse immediately for at Get medical attention if symptoms occur.	least 15 minutes with	plenty of water.		
SKIN:	Wash affected areas thoroughly with soap and water. Ge	t medical attention if s	symptoms occur.		
INHALATION:	Remove the affected individual into fresh air and keep th necessary. Get medical attention if symptoms occur.	e person calm. Assist	in breathing if		
INGESTION:	Rinse mouth and then drink plenty of water. Do not inductive anything by mouth if the victim is unconscious or har if symptoms occur.				
NOTES TO PHYSICIAN:	Symptomatic and supportive therapy as needed. Followishould be monitored for 48 hours.	ing severe exposure,	medical follow-up		
SECTION 5: FIRE FIGHTING MEA	SURES				
FLASH POINT:	352°F (178°C).				
HAZARDS WHEN ON FIRE OR NEAR FLAME:	May produce toxic fumes of carbon dioxide and carbon m When in a closed container, pressure will increase which	nonoxide when near h may lead to a rupture	neat source/flame. of the container.		
SUITABLE EXTINGUISHING MEDIA:	Dry chemical foam, carbon dioxide, foam, or water spray	(mist/fog) to extinguis	h.		
UNSUITABLE EXTINGUISHING MEDIA:	None known.				
SPECIAL EXPOSURE HAZARDS:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. If in a fire or heated, a pressure increase will occur and the container may rupture.				
SPECIAL PROTECTIVE EQUIPMENT FOR FIRE FIGHTERS:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. PVC boots, gloves, safety helmet and protective clothing should be worn.				
SECTION 6: ACCIDENTAL RELEAS	SE MEASURES				
ACCIDENTAL RELEASE MEASURES:	For major spills call CHEMTREC : Toll free 1-800-424-930 1-703-527-3887 .	ofor international cal	I		
PERSONAL PRECAUTIONS:	Wear appropriate personal protective equipment recommended in SECTION 8: EXPOSURE CONTROL/ PERSONAL PROTECTION of this SDS. Immediately contact emergency personnel. Evacuate the area. Kee upwind avoiding inhalation of vapors. Clean-up should only be performed by trained personnel. People dealing with major spillages should wear full protective clothing including respiratory protection.				
ENVIRONMENTAL PRECAUTIONS:	This material may contaminate the environment without proper control and response to spills. Ensure spilled material does not come in contact with soil, waterway, drains, sewers, or other runoff that would further disperse the material. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil, or air). Sources of ignition should be kept clear.				
METHODS FOR CONTAINMENT:	Use diking or capping to control migration. Contain and absorb large spillages with a non-flammable absorbent carrier (such as vermiculite, earth, or sand). DO NOT USE combustible materials such as sawdust. Shovel into open-top drums or plastic bags for further decontamination, if necessary. Remove and properly dispose of residues. Dispose of via a licensed waste disposal contractor (See SECTION 13: DISPOSAL CONSIDERATIONS) Notify applicable government authorities if release is reportable.				
METHODS FOR CLEANING UP:	Only proceed with clean up by taking the appropriate personal protection measures required and ensure surrounding area does not contain further hazards that could worsen the spill, cause migration, or cause further harm (i.e. eliminate any ignition sources). Move any non-contaminated, non-leaking containers from the spill zone if it can be done safely. Dike, dam, or further restrict and stop active leaks without posing further damage or harm to individuals, the environment, and/or structures. Contain and collect spillage. See SECTION 13: DISPOSAL CONSIDERATIONS for disposal information and SECTION 8: EXPOSURE CONTROL/ PERSONAL PROTECTION for recommended Personal Protective Equipment (PPE). Obey all local, state, and federal regulations during clean up.				

SECTION 7: HANDLING & STOR	RAGE		
GENERAL:	Ideal storage temperature is 60-90°F (15-32°C). Handling and storage shall be in accordance with local, state/provincial, or federal regulations.		
HANDLING:	Before opening this package, read and follow warning labels on all components. Avoid contact with the product or reaction mixture. Put on appropriate personal protective equipment. Use only with adequate ventilation to ensure that the occupational exposure limit is not exceeded, use respirator when ventilation is inadequate. Avoid breathing aerosols, mists, and vapors. (See SECTION 8: EXPOSURE CONTROL/ PERSONAL PROTECTION for details). Do not ingest. Eating, drinking, and smoking shall be prohibited in areas where this material is handled, stored, and processed. Workers shall wash hands and face before eating, drinking, and smoking. Persons with a history of skin sensitization problems, asthma, allergies, or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Do not get in eyes, on skin, or clothing. Keep in the original container or an approved alternative made from a compatible material. Keep tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse containers.		
STORAGE:	Keep container tightly closed and properly sealed when stored. When possible, store product indoors in a dry, well-ventilated area. Store in original container, away from incompatible materials, and away from food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers and use appropriate containment to avoid environmental contamination.		
SECTION 8: EXPOSURE CONTI	ROLS/PERSONAL PROTECTION		
EXPOSURE LIMITS:	As of the latest revision of this document, no known exposure limits exist for this product. The absence of current exposure data does not relieve an employer, user, or other to determine the specific hazards and appropriate exposure protection measures in the application and use of this product. Personal, workplace, atmospheric, and/or biological monitoring may be required to determine the effectiveness of engineering, administrative, and/or other best practice control measures. These monitoring results determine the need for and type of respiratory protective equipment, if any. Refer to the appropriate local, state, and federal regulations and statutes for the most current information and for guidance in the determination of hazardous conditions and the correlating personal protective equipment.		
ENGINEERING CONTROLS:	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor, or mist, use process enclosures, local exhaust ventilation, and other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.		
HYGIENE MEASURES:	Wash hands, forearms, and face thoroughly with plenty of soap and water after handling chemical products, before eating, smoking, and using the restroom and at the end of the working period. Appropriate engineering, administrative, and other best practice decontamination control measures must be used to isolate contaminates on clothing and to prevent unintended migration of contaminants. Handle clothing and other potentially contaminated material appropriately and in compliance with local, state, and federal regulations in the process of removing, washing/cleaning, and reuse of these potentially contaminated materials. Ensure compliant use and location of eyewash station and safety showers.		
PERSONAL PROTECTIVE EQUIPMENT	(PPE):		
EYE PROTECTION:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield.		
SKIN PROTECTION:	Personal protective equipment for the body should be selected based on the task being performed, the risks involved, and should be approved by an industrial hygiene specialist before handling this product.		
HANDS PROTECTION:	Chemical resistant gloves complying with applicable health and safety standards shall be worn when handling this product. Protective gloves are those made from butyl rubber, nitrile rubber, or polyvinyl alcohol. Appropriate hazard assessments in conjunction with an evaluation of the protection factors of chemical resistant gloves shall be performed to ensure the protective properties remain intact. It is noted that the time it takes to breakdown of protection factors for different glove manufacturers varies. In the case of mixtures, the protection factors of chemical resistant gloves may be impacted and deteriorate at unpredictable rates without understanding the impact of the substance and the specific protection factors of the chemical resistant gloves.		
RESPIRATORY PROTECTION:	Ensure adequate ventilation. If the respirator is the sole means of protection, use a full-face supplied respirator. Use respirators and components tested and approved under appropriate government standards such as OSHA 29CFR 1910.134, NIOSH (US), or CEN (EU).		
ENVIRONMENTAL EXPOSURE CONTROLS:	Dispose of raw and spent materials and wastes in compliance with all local, state, and federal regulations to prevent potential environmental contamination. Industrial air monitoring may be required to determine any potential environmental hazards to the atmosphere. This monitoring may result in the use of engineering and administrative controls such as filtering and scrubbing systems to mitigate or eliminate potential contaminants.		

SECTION 9: PHYSICAL & C	HEMICAL PROPERT	TIES			
PHYSICAL STATE:	Liquid	1	FLASH POINT:		352°F (178°C)
COLOR:	Clear	1	AUTO-IGNITION TEMPERATURE:		No Data
ODOR:	Amine odor	1	DECOMPOSIT	TION TEMPERATURE:	No Data
ODOR THRESHOLD:	No Data	1	EXPLOSIVE LI	MITS:	Not explosive
pH:	No Data	ı	FLAMMABILIT	ГҮ:	No Data
WATER SOLUBILITY:	No Data	I	BOILING POIN	NT:	No Data
PARTITION COEFFICIENT:	No Data	1	BOILING RAN	GE:	No Data
SPECIFIC GRAVITY:	1.003±0.005 g/cc @ 77°F	(25°C)	MELTING/FRE	EZING POINT:	No Data
VISCOSITY:	350±25 mPa.s @ 77°F (25	5°C) '	VAPOR PRES	SURE:	No Data
EVAPORATION RATE:	No Data	,	VAPOR DENS	ITY:	No Data
VOC:	0 g/L	ı	RELATIVE DEI	NSITY:	8.35±0.05 lbs/gal
SECTION 10: STABILITY &	REACTIVITY				
STABILITY:	Stable when handled an	d stored at	temperatures	60-90°F (15-32°C).	
INCOMPATIBILITY:	Strong reaction with acid	ds and oxidi	izing agents.		
HAZARDOUS REACTION:	No specific data available	e.			
HAZARDOUS POLYMERIZATION:	Hazardous polymerizatio	on will not o	occur under no	rmal conditions of storage	e and use.
CONDITIONS TO AVOID:	Avoid temperatures above	e 100°F (38°C	C) and freezing	temperatures. Avoid moist	ure contamination in containers.
HAZARDOUS DECOMPOSITION:	Combustion of product wi	II lead to oxi	ides of nitroger	n, carbon dioxide, and carbo	on monoxide being produced.
SECTION 11: TOXICOLOGY	INFORMATION				
ACUTE HEALTH EFFECTS:			_		
EYE CONTACT:	Not available.				
SKIN CONTACT:	Not available.				
INHALATION:	Not available.				
INGESTION:	Not available.				
ACUTE TOXICITY:					
COMPONENT NAME	CAS NUMBER	LD ₅₀ Or	al (mg/kg)	LD ₅₀ Dermal (mg/kg)	LC ₅₀ Inhalation (mg/L/4hrs)
Polyoxypropylenediamine	9046-10-0	2,88	35 (rat)	2,980 (rabbit)	0.37 (rat)
Diethylmethylbenzenediamine	68479-98-1	738	8 (rat)	>2,017 (rat)	Not available
Glyceryl poly (oxypropylene) triamine	64852-22-8	2,69	90 (rat)	12,500(rabbit)	Not available
POTENTIAL CHRONIC EFFECTS:					
CHRONIC EFFECTS:	C EFFECTS: A two year study on rats showed that diethylmethylbenzenediamine caused effects in the pancreas, liver, thyroid, and eyes. There was an increase in the number of tumors in the liver and thyroid of male rats. An increase in the number of tumors in the liver and possibly mammary glands of female rats was also found.				
TARGET ORGANS:	Pancreas, liver, thyroid, a	and eyes.			
CARCINOGENICITY:	As of this publication, this material is not listed on the National Toxic Program (NTP) Report of Carcinogens. Please refer to the most recent information with NTP.				
MUTAGENICITY:	No known significant eff	ects or critic	cal hazards.		
TERATOGENICITY:	No known significant eff	ects or criti	cal hazards.		
FERTILITY EFFECTS:	No known significant eff	ects or criti	cal hazards.		
DEVELOPMENTAL EFFECTS:	No known significant eff	ects or criti	cal hazards.		
MEDICAL CONDITIONS AGGRAVATED BY OVER-EXPOSURE:	No known significant eff	ects or criti	cal hazards.		

SECTION 12: ECOLOGICAL INFORMATION		
COMPONENT ECOTOXICITY		
Polyoxypropylenediamine	96 Hr LC50 Oncorhynchus mykiss: > 15 mg/L [semistatic] 48 Hr EC50 Daphnia magna: 80 mg/L [static] 96 Hr ErC50 Pseudokirchneriella subcapitata: > 15 mg/L	
Diethylmethylbenzenediamine	96 Hr LC50 fish: > 104 mg/L 48 Hr EC50 water flea: 5.8 mg/L 72 Hr EC50 algae: 104 mg/L	
Glyceryl poly (oxypropylene) triamine	96 Hr LC50 fish: 68 mg/L	

SECTION 13: DISPOSAL CONSIDERATION

۷	۷	Ά	Sī	ſΕ	D	ISP	O	S	Α	L:

By-product wastes or process waste generation should be eliminated and/or minimized when possible. Do not dispose of any contaminants into sanitary sewer systems, storm drains, Publicly Owned Treatment Works (POTW), or any other municipal waste water treatment facility without written approval and agreements for processing wastes with such enterprises. Dispose of raw or unused materials, wastes, and/or by-products in accordance with all applicable local, state, and federal laws. Employ the expertise and knowledge of qualified personnel or contractors in disposal of any and all variants of this product. Ensure material containers are cleaned to the applicable standards before recycling, disposing, or reusing containers. Take special precautions to avoid any cross contamination and potential unknown effects from mixing with other substances. Refer to SECTION 8: EXPOSURE CONTROL/ PERSONAL PROTECTION of this document for personal protection requirements. Disposal to the environment or in violation of environmental protection laws and statutes must be prevented.

SECTION 14: TRANSPORT INFORMATION

PROPER SHIPPING NAME		
DOT:	Not regulated	
TDG:	Not regulated	
IMDG:	Not regulated	
IATA:	Not regulated	

This product could potentially contaminate aquatic and terrestrial environments if not handled in accordance with all precautions, regulations, and laws. Users, transporters, and all other applicable entities must review, follow, and apply any and all necessary precautions and procedures to eliminate and/or minimize potential hazards or risks to aquatic or terrestrial environments.

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS					
TSCA 8b Inventory:	All components are listed on the TSCA inventory or are exempt.				
TSCA 5a (2):	No components listed.				
TSCA 5e:	No components listed.				
TSCA 12b:	No components listed.				
Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs):	No components listed.				
Clean Air Act - Ozone Depleting Substances (ODS):	This product does not contain nor is i	This product does not contain nor is it manufactured with ozone depleting substances.			
SARA 313 Form R - Reporting	COMPONENT	CAS NUMBER	CONCENTRATION		
Requirements:	Diethylmethylbenzenediamine	68479-98-1	20-40%		
SARA 311/312 hazard identification:	Immediate (acute) health hazard. Delayed (chronic) health hazard.				
CERCLA Hazardous substances:	No components listed.				
STATE REGULATIONS:					
PENNSYLVANIA/NEW JERSEY/ MASSACHUSETTS - RTK:	No components listed.				
California Prop 65:	This product contains no listed substances known to the State of California to cause cancer, birth defects, or other reproductive harm, at levels which would require a warning under the statute.				
CANADA					
WHMIS (Canada):	WHMIS Class D-1B: Material causing immediate and serious toxic effects (toxic). WHMIS Class E: Corrosive.				
CEPA DSL:	All components are listed or exempted.				
This product has been classified in acco	rdance with the hazard criteria of the	Controlled Products Regulat	ions and the SDS contains all		

the information required by the Controlled Products Regulations.

INTERNATIONAL LISTS:				
Australia inventory (AICS):	Australian Inventory of Chemical Substances	All components are listed or exempted.		
Canada inventory:	Canada Domestic Substance List	All components are listed or exempted.		
Canada inventory:	Canada Non-Domestic Substance List	All components are listed or exempted.		
China inventory (IECSC):	China Inventory of Existing Chemical Substances	All components are listed or exempted.		
EU inventory:	EU REACH List of Registered Intermediates	All components are listed or exempted.		
EU inventory:	EU REACH List of Pre-Registered Substances	All components are listed or exempted.		
EU inventory:	EU REACH List of Registered Substances	All components are listed or exempted.		
Japan inventory:	Japanese Existing and New Chemical Substances List	All components are listed or exempted.		
South Korea inventory:	South Korea Existing Chemicals Inventory	All components are listed or exempted.		
Phillipines inventory (PICCS):	Phillippines Inventory of Chemicals and Chemical	All components are listed or exempted.		

SECTION 16: OTHER INFORMATION

NFPA & HMIS 4 Extreme 3 Serious 2 Moderate 1 Slight 0 No Hazard



National Fire Protection Association (NFPA)





Hazardous Material Information System (HMIS)

HEALTH	3
FLAMMABILITY	1
REACTIVITY	0
SPECIAL	
INFORMATION	

Note: The customer is responsible for determining the PPE code for this material. At the time of publishing, the NFPA/HMIS and the New GHS scale had opposite scales of severity. Check the most recent publications for current information.

For Your Protection:	The information and recommendations in this publication is to the best of our knowledge, reliable. The toxicity and risk characteristics of products made by SPI will necessarily differ from the toxicity and risk characteristics that occur when such products are used with other materials during a manufacturing process. The resulting risk characteristics should be determined and made known to ultimate end-users and processors. The user is responsible to comply with all applicable federal, provincial or municipal laws and regulations. SPI MAKES NO WARRANTIES OF ANY KIND, EXPRESSED OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.
Preparation Information:	This SDS supersedes ALL previous SDS versions.